ELECTRONIC CODE OF FEDERAL REGULATIONS

e-CFR data is current as of April 17, 2015

Title 47 → Chapter I → Subchapter D → Part 90 → Subpart R

Title 47: Telecommunication

PART 90-PRIVATE LAND MOBILE RADIO SERVICES

Subpart R—Regulations Governing the Licensing and Use of Frequencies in the 763-775 and 793-805 MHz Bands

Contents §90.521 Scope. §90.523 Eligibility §90.525 Administration of interoperability channels. §90.527 Regional plan requirements. §90.529 State License. §90.531 Band plan. §90.532 Licensing of the 758-769 MHz and 788-799 MHz Bands. §90.533 Transmitting sites near the U.S./Canada or U.S./Mexico border. §90.535 Modulation and spectrum usage efficiency requirements. §90.537 Trunking requirement. §90.539 Frequency stability §90.541 Transmitting power and antenna height limits. §90.542 Broadband transmitting power limits. §90.543 Emission limitations. §90.547 Narrowband Interoperability channel capability requirement. §90.548 Interoperability Technical Standards. §90.549 Transmitter certification §90.551 Construction requirements. §90.553 Encryption. §90.555 Information exchange. §90.557 Secondary fixed signaling operations. §90.559 Station Identification.

Source: 63 FR 58651, Nov. 2, 1998, unless otherwise noted.

♣ Back to Top

§90.521 Scope.

This subpart sets forth the regulations governing the licensing and operations of all systems operating in the 758-775 MHz and 788-805 MHz frequency bands. It includes eligibility, operational, planning and licensing requirements and technical standards for stations licensed in these bands. The rules in this subpart are to be read in conjunction with the applicable requirements contained elsewhere in this part; however, in case of conflict, the provisions of this subpart shall govern with respect to licensing and operation in these frequency bands.

[63 FR 58651, Nov. 2, 1998, as amended at 72 FR 48860, Aug. 24, 2007; 77 FR 62463, Oct. 15, 2012]

♣ Back to Top

§90.523 Eligibility.

This section implements the definition of public safety services contained in 47 U.S.C. 337(f)(1). The following are eligible to hold Commission authorizations for systems operating in the 769-775 MHz and 799-805 MHz frequency bands:

- (a) State or local government entities. Any territory, possession, state, city, county, town, or similar State or local governmental entity is eligible to hold authorizations in the 764-776 MHz and 794-806 MHz frequency bands.
- (b) Nongovernmental organizations. A nongovernmental organization (NGO) that provides services, the sole or principal purpose of which is to protect the safety of life, health, or property, is eligible to hold an authorization for a system operating in the 764-776 MHz and 794-806 MHz frequency bands for transmission or reception of communications essential to providing such services if (and only for so long as) the NGO applicant/licensee:
- (1) Has the ongoing support (to operate such system) of a state or local governmental entity whose mission is the oversight of or provision of services, the sole or principal purpose of which is to protect the safety of life, health, or property;
- (2) Operates such authorized system solely for transmission of communication essential to providing services the sole or principal purpose of which is to protect the safety of life, health, or property; and
- (3) All applications submitted by NGOs must be accompanied by a new, written certification of support (for the NGO applicant to operate the applied-for system) by the state or local governmental entity referenced in paragraph (b)(1) of this section.

- (c) All NGO authorizations are conditional. NGOs assume all risks associated with operating under conditional authority. Authorizations issued to NGOs to operate systems in the 764-776 MHz and 794-806 MHz frequency bands include the following condition: If at any time the supporting governmental entity (see paragraph (b)(1)) notifies the Commission in writing of such governmental entity's termination of its authorization of a NGO's operation of a system in the 764-776 MHz and 794-806 MHz frequency bands, the NGO's application shall be dismissed automatically or, if authorized by the Commission, the NGO's authorization shall terminate automatically.
- (d) Paragraphs (a) and (b) notwithstanding, no entity is eligible to hold an authorization for a system operating in the 764-776 MHz and 794-806 MHz frequency bands on the basis of services, the sole or principal purpose of which is to protect the safety of life, health or property, that such entity makes commercially available to the public.
 - (e) A nationwide license for the 758-769 MHz and 788-799 MHz bands shall be issued to the First Responder Network Authority.

[63 FR 58651, Nov. 2, 1998, as amended at 65 FR 53645, Sept. 5, 2000; 72 FR 48860, Aug. 24, 2007; 79 FR 600, Jan. 6, 2014]

& Back to Top

§90.525 Administration of interoperability channels.

- (a) States are responsible for administration of the Interoperability channels in the 769-775 MHz and 799-805 MHz frequency bands. Base and control stations must be licensed individually. A public safety entity meeting the requirements of §90.523 may operate mobile or portable units on the Interoperability channels in the 769-775 MHz and 799-805 MHz frequency bands without a specific authorization from the Commission provided it holds a part 90 license. All persons operating mobile or portable units under this authority are responsible for compliance with part 90 of these rules and other applicable federal laws.
- (b) License applications for Interoperability channels in the 769-775 MHz and 799-805 MHz frequency bands must be approved by a state-level agency or organization responsible for administering state emergency communications. States may hold the licenses for Interoperability channels or approve other qualified entities to hold such licenses. States may delegate the approval process for interoperability channels to another entity, such as regional planning committees.

[72 FR 48860, Aug. 24, 2007]

& Back to Top

§90.527 Regional plan requirements.

Each regional planning committee must submit a regional plan for approval by the Commission.

- (a) Common elements. Regional plans must incorporate the following common elements:
- (1) Identification of the document as the regional plan for the defined region with the names, business addresses, business telephone numbers, and organizational affiliations of the chairpersons and all members of the planning committee.
- (2) A summary of the major elements of the plan and an explanation of how all eligible entities within the region were given an opportunity to participate in the planning process and to have their positions heard and considered fairly.
- (3) A general description of how the spectrum would be allotted among the various eligible users within the region with an explanation of how the requirements of all eligible entities within the region were considered and, to the degree possible, met.
 - (4) An explanation as to how needs were assigned priorities in areas where not all eligible entities could receive licenses.
 - (5) An explanation of how the plan had been coordinated with adjacent regions.
- (6) A detailed description of how the plan put the spectrum to the best possible use by requiring system design with minimum coverage areas, by assigning frequencies so that maximum frequency reuse and offset channel use may be made, by using trunking, and by requiring small entities with minimal requirements to join together in using a single system where possible.
- (7) A detailed description of the future planning process, including, but not limited to, amendment process, meeting announcements, data base maintenance, and dispute resolution.
- (8) A certification by the regional planning chairperson that all planning committee meetings, including subcommittee or executive committee meetings, were open to the public.
- (b) Modification of regional plans. Regional plans may be modified by submitting a written request, signed by the regional planning committee, to the Chief, Public Safety and Homeland Security Bureau. The request must contain the full text of the modification. Modifications are considered either major or minor. Regional planning committees must certify that successful coordination with all adjacent regions has occurred for major modifications and that all such regions concur with the major modification. Unless requested otherwise by the regional planning committee, the Bureau will only place major modifications on public notice for comment.
- (1) Except as noted below, modifications changing the way channels are allocated, allotted or coordinated are considered major modifications.
 - (2) Modifications changing how channels are allotted are considered minor modifications only if:
 - (i) The proposed channel change or channel addition involves a facility located more than seventy miles from the adjacent region border;
- (ii) The co-channel or adjacent channel interference contour of the facility changing or adding the channel does not intersect the border of an adjacent region, or
 - (iii) The proposed channel change or channel addition has been coordinated in writing with any affected adjacent region.
 - (3) Changes in membership or leadership of regional planning committees are considered minor modifications.

[63 FR 58651, Nov. 2, 1998, as amended at 79 FR 39339, July 10, 2014]

& Back to Top

§90.529 State License.

- (a) Narrowband channels designated as state channels in §90.531 are licensed to each state (as defined in §90.7) as follows:
- (1) Each state that chooses to take advantage of the spectrum designated as state channels must file an application for up to 2.4 megahertz of this spectrum no later than December 31, 2001. For purposes of this section, the elected chief executive (Governor) of each state, or his or her designee, shall be deemed the person authorized to apply for the State License.
- (2) What ever part of this 2.4 megahertz that a state has not applied for by December 31, 2001, will revert to General Use and be administered by the relevant RPC (or RPCs in the instances of states that encompass multiple RPCs).
 - (b) Each state license will be granted subject to the condition that the state certifies on or before each applicable benchmark date that it is:
- (1) Providing or prepared to provide "substantial service" to one-third of their population or territory by June 13, 2014, i.e., within five years of the date that incumbent broadcasters are required to relocate to other portions of the spectrum;
- (2) Providing or prepared to provide "substantial service" to two-thirds of their population or territory by June 13, 2019, i.e., within ten years of the date that incumbent broadcasters are required to relocate to other portions of the spectrum.
- (2) providing or prepared to provide "substantial service" to two-thirds of their population or territory by January 1, 2017, i.e., within ten years of the date that incumbent broadcasters are required to relocate to other portions of the spectrum.
- (c) The Commission will deem a state "prepared to provide substantial service" if the licensee certifies that a radio system has been approved and funded for implementation by the deadline date. "Substantial service" refers to the construction and operation of 700 MHz facilities by public safety entities providing service which is sound, favorable, and substantially above a level of mediocre service which just might minimally warrant renewal.
- (d) If a state licensee fails to meet any condition of the grant the state license is modified automatically to the frequencies and geographic areas where the state certifies that it is providing substantial service.
- (e) Any recovered state license spectrum will revert to General Use. However, spectrum licensed to a state under a state license remains unavailable for reassignment to other applicants until the Commission's database reflects the parameters of the modified state license.

[65 FR 66654, Nov. 7, 2000, as amended at 79 FR 20106, Apr. 11, 2014]

♣ Back to Top

§90.531 Band plan.

This section sets forth the band plan for the 758-775 MHz and 788-805 MHz public safety bands.

- (a) Base and mobile use. The 763-775 MHz band may be used for base, mobile or fixed (repeater) transmissions. The 793-805 MHz band may be used only for mobile or fixed (control) transmissions.
- (b) Narrowband segments. There are two band segments that are designated for use with narrowband emissions. Each of these narrowband segments is divided into 960 channels having a channel size of 6.25 kHz as follows:

Frequency range	Channel Nos.	
769-775 MHz	1-960	
799-805 MHz	961-1920	

- (1) Narrowband interoperability channels. The following narrowband channels are designated for nationwide interoperability licensing and use: 23, 24, 39, 40, 63, 64, 79, 80, 103, 104, 119, 120,143, 144, 159, 160, 183, 184, 199, 200, 223, 224, 239, 240, 263, 264, 279, 280, 303, 304, 319, 320, 641, 642, 657, 658, 681, 682, 697, 698, 721, 722, 737, 738, 761, 762, 777, 778, 801, 802, 817, 818, 841, 842, 857, 858, 881, 882, 897, 898, 921, 922, 937, 938, 983, 984, 999, 1000, 1023, 1024, 1039, 1040, 1063, 1064, 1079, 1080, 1103, 1104, 1119, 1120, 1143, 1144, 1159, 1160, 1183, 1184, 1199, 1200, 1223, 1224, 1239, 1240, 1263, 1264, 1279, 1280, 1601, 1602, 1617, 1618, 1641, 1642, 1657, 1658, 1681, 1682, 1697, 1698, 1721, 1722, 1737, 1738, 1761, 1762, 1777, 1778, 1801, 1802, 1817, 1818, 1841, 1842, 1857, 1858, 1881, 1882, 1897, 1898.
- (i) Narrowband data Interoperability channels. The following channel pairs are reserved nationwide for data transmission on a primary basis: 279/1239, 280/1240, 921/1881, and 922/1882. Voice operations are permitted on these channels on a secondary basis.
- (ii) Narrowband calling Interoperability channels. The following channel pairs are dedicated nationwide for the express purpose of Interoperability calling only: 39/999, 40/1000, 681/1641, and 682/1642. They may not be used primarily for routine, day-to-day communications. Encryption is prohibited on the designated calling channels.
- (iii) Narrowband trunking Interoperability channels. The following Interoperability channel pairs may be used in trunked mode on a secondary basis to conventional Interoperability operations: 23/983, 24/984, 103/1063, 104/1064, 183/1143, 184/1144, 263/1223, 264/1224, 657/1617, 658/1618, 737/1697, 738/1698, 817/1777, 818/1778, 897/1857, 898/1858. For every ten general use channels trunked at a station, entities may obtain a license to operate in the trunked mode on two of the above contiguous Interoperability channel pairs. The maximum number of Interoperability channel pairs that can be trunked at any one location is eight.
- (2) Narrowband General Use Reserve channels. The following narrowband channels are designated for General Use subject to Commission approved regional planning committee regional plans and technical rules applicable to General Use channels: 37, 38, 61, 62, 77, 78, 117, 118, 141, 142, 157, 158, 197, 198, 221, 222, 237, 238, 277, 278, 301, 302, 317, 318, 643, 644, 683, 684, 699, 700, 723, 724, 763, 764, 779, 780, 803, 804, 843, 844, 859, 860, 883, 884, 923, 924, 939, 940, 997, 998, 1021, 1022, 1037, 1038, 1077, 1078, 1101, 1102, 1117, 1118, 1157, 1158, 1181, 1182, 1197, 1198, 1237, 1238, 1261, 1262, 1277, 1278, 1603, 1604, 1643, 1644, 1659, 1660, 1683, 1684, 1723, 1724, 1739, 1740, 1763, 1764, 1803, 1804, 1819, 1820, 1843, 1844, 1883, 1884, 1899, 1900.
- (i) *T-Band Relocation*. The narrowband channels established in paragraph (b)(2) are designated for priority access by public safety incumbents relocating from the 470-512 MHz band in the urban areas specified in §§90.303 and 90.305 of the Commission's rules provided that

such incumbent commits to return to the Commission an equal amount of T-Band spectrum and obtains concurrence from the relevant regional planning committee(s). Public safety T-Band incumbents shall enjoy priority access for a five year period starting from the date the Public Safety and Homeland Security Bureau releases a public notice announcing the availability of Reserve Channels for licensing.

- (ii) Deployable Trunked Systems. Outside the urban areas specified in §§90.303 and 90.305 of the Commission's rules, the 700 MHz Regional Planning Committees may designate no more than eight 12.5 kilohertz channel pairs for temporary deployable mobile trunked infrastructure (F2BT) that could be transported into an incident area to assist with emergency response and recovery.
- (iii) General Use. Outside the urban areas specified in §§90.303 and 90.305 of the Commission's rules, the 700 MHz Regional Planning Committees may designate sixteen to twenty four 12.5 kilohertz channel pairs for General Use, including low power vehicular mobile repeaters (MO3).
- (3) Narrowband low power channels subject to regional planning. The following narrowband channels are designated for low power use for on-scene incident response purposes using mobiles and portables subject to Commission-approved regional planning committee regional plans. Transmitter power must not exceed 2 watts (ERP): Channels 1-8 paired with Channels 961-968, and Channels 949-958 paired with Channels 1909-1918.
- (4) Narrowband low power itinerant channels. The following narrowband channels are designated for low power use for on-scene incident response purposes using mobiles and portables. These channels are licensed nationwide for itinerant operation. Transmitter power must not exceed 2 watts (ERP): Channels 9-12 paired with Channels 969-972 and Channels 959-960 paired with Channels 1919-1920.
- (5) Narrowband state channels. The following narrowband channels are designated for direct licensing to each state (including U.S. territories, districts, and possessions): 25-36, 65-76, 105-116, 145-156, 185-196, 225-236, 265-276, 305-316, 645-656, 685-696, 725-736, 765-776, 805-816, 845-856, 885-896, 925-936, 985-996, 1025-1036, 1065-1076, 1105-1116, 1145-1156, 1185-1196, 1225-1236, 1265-1276, 1605-1616, 1645-1656, 1685-1696, 1725-1736, 1765-1776, 1805-1816, 1845-1856, 1885-1896. Voice operations on these channels are subject to compliance with the spectrum usage efficiency requirements set forth in §90.535(d).
- (6) Narrowband general use channels. All narrowband channels established in this paragraph (b), other than those listed in paragraphs (b) (1), (b)(4), (b)(5), and (b)(7) of this section are reserved to public safety eligibles subject to Commission approved regional planning committee regional plans. Voice operations on these channels are subject to compliance with the spectrum usage efficiency requirements set forth in §90.535(d).
- (7) Air-ground channels. The following channels are reserved for air-ground communications to be used by low-altitude aircraft and ground based stations: 21/981, 22/982, 101/1061, 102/1062, 181/1141, 182/1142, 261/1221, 262/1222, 659/1619, 660/1620, 739/1699, 740/1700, 819/1779, 820/1780, 899/1859, and 900/1860.
 - (i) Airborne use of these channels is limited to aircraft flying at or below 457 meters (1500 feet) above ground level.
 - (ii) Aircraft are limited to 2 watts effective radiated power (ERP) when transmitting while airborne on these channels.
 - (iii) Aircraft may transmit on either the mobile or base transmit side of the channel pair.
 - (iv) States are responsible for the administration of these channels.
 - (c) [Reserved]
- (d) Combining channels. Except as noted in this section, at the discretion of the appropriate regional planning committee, contiguous channels may be used in combination in order to accommodate requirements for larger bandwidth emissions, in accordance with this paragraph. Interoperability channels may not be combined with channels in another group except for channels for secondary trunking channels.
- (1) Narrowband. Subject to compliance with the spectrum usage efficiency requirements set forth in §90.535, two or four contiguous narrowband (6.25 kHz) channels may be used in combination as 12.5 kHz or 25 kHz channels, respectively. The lower (in frequency) channel for two channel combinations must be an odd (i.e., 1, 3, 5 * * *) numbered channel. The lowest (in frequency) channel for four channel combinations must be a channel whose number is equal to 1+(4xn), where n = any integer between 0 and 479, inclusive (e.g., channel number 1, 5, * * 1917). Channel combinations are designated by the lowest and highest channel numbers separated by a hyphen, e.g., "1-2" for a two channel combination and "1-4" for a four channel combination.
 - (2) [Reserved]
- (e) Channel pairing. In general, channels must be planned and assigned in base/mobile pairs that are separated by 30 MHz. However, until December 31, 2006, channels other than those listed in paragraphs (b)(1) and (c)(1), may be planned and assigned in base/mobile pairs having a different separation, where necessary because 30 MHz base/mobile pairing is precluded by the presence of one or more co-channel or adjacent channel TV/DTV broadcast stations.
 - (f) Internal guard band. The internal guard band (768-769/798-799 MHz) is reserved.
 - (g) Broadband. The 758-768 MHz and 788-798 MHz bands are allocated for broadband communications.

[63 FR 58651, Nov. 2, 1998, as amended at 65 FR 66654, Nov. 7, 2000; 66 FR 10635, 10636, Feb. 16, 2001; 67 FR 61005, Sept. 27, 2002; 67 FR 76700, Dec. 13, 2002; 72 FR 48860, Aug. 24, 2007; 77 FR 62463, Oct. 15, 2012; 79 FR 71325, Dec. 2, 2014]

EFFECTIVE DATE NOTE: At 79 FR 71325, Dec. 2, 2014, §90.531(b)(2) and (b)(7) were revised. These paragrapghs contain information collection and recordkeeping requirements and will not become effective until approval has been given by the Office of Management and Budget.

♠ Back to Top

§90.532 Licensing of the 758-769 MHz and 788-799 MHz Bands.

Pursuant to Section 6201 of the Middle Class Tax Relief and Job Creation Act of 2012, Public Law 112-96, 126 Stat. 156 (2012), a nationwide license for use of the 758-769 MHz and 788-799 MHz bands shall be issued to the First Responder Network Authority for a initial license term of ten years from the date of the initial issuance of the license. Prior to expiration of the term of such initial license, the First Responder Network Authority shall submit to the Commission an application for the renewal of such license. Such renewal application shall

demonstrate that, during the preceding license term, the First Responder Network Authority has met the duties and obligations set forth under the foregoing Act. A renewal license shall be for a term not to exceed ten years.

[77 FR 62463, Oct. 15, 2012]

♣ Back to Top

§90.533 Transmitting sites near the U.S./Canada or U.S./Mexico border.

This section applies to each license to operate one or more public safety transmitters in the 758-775 MHz and 788-805 MHz bands, at a location or locations North of Line A (see §90.7) or within 120 kilometers (75 miles) of the U.S.-Mexico border, until such time as agreements between the government of the United States and the government of Canada or the government of the United States and the government of Mexico, as applicable, become effective governing border area non-broadcast use of these bands. Public safety licenses are granted subject to the following conditions:

- (a) Public safety transmitters operating in the 758-775 MHz and 788-805 MHz bands must conform to the limitations on interference to Canadian television stations contained in agreement(s) between the United States and Canada for use of television channels in the border area.
- (b) Public safety facilities must accept any interference that may be caused by operations of UHF television broadcast transmitters in Canada and Mexico.
- (c) Conditions may be added during the term of the license, if required by the terms of international agreements between the government of the United States and the government of Mexico, as applicable, regarding non-broadcast use of the 758-775 MHz and 788-805 MHz bands.

[43 FR 54791, Nov. 22, 1978, as amended at 67 FR 76700, Dec. 13, 2002; 72 FR 48861, Aug. 24, 2007; 79 FR 600, Jan. 6, 2014]

♣ Back to Top

§90.535 Modulation and spectrum usage efficiency requirements.

Transmitters designed to operate in 769-775 MHz and 799-805 MHz frequency bands must meet the following modulation standards:

- (a) All transmitters in the 769-775 MHz and 799-805 MHz frequency bands must use digital modulation. Mobile and portable transmitters may have analog modulation capability only as a secondary mode in addition to its primary digital mode except on the interoperability channels listed in §90.531(b)(1). Analog modulation is prohibited on the interoperability channels. Mobile and portable transmitters that only operate on the low power channels designated in §90.531(b)(3) and (4) are exempt from this digital modulation requirement.
- (b) Transmitters designed to operate in the narrowband segment using digital modulation must be capable of maintaining a minimum data (non-voice) rate of 4.8 kbps per 6.25 kHz of bandwidth.
- (c) Transmitters designed to operate in the wideband segment using digital modulation must be capable of maintaining a minimum data (non-voice) rate of 384 kbps per 150 kHz of bandwidth.
- (d) Transmitters designed to operate on the channels listed in paragraphs §90.531(b)(2), (b)(5), (b)(6), and (b)(7) must be capable of operating in the voice mode at an efficiency of at least one voice path per 12.5 kHz of spectrum bandwidth.
- (1) With the exception of licensees designated in paragraph (d)(2) of this section, after December 31, 2014, licensees may only operate in voice mode in these channels at a voice efficiency of at least one voice path per 6.25 kHz of spectrum bandwidth.
- (2) Licensees authorized to operate systems in the voice mode on these channels from applications filed on or before December 31, 2014, may continue operating in voice mode on these channels (including modification applications of such licenses granted after December 31, 2014, for expansion or maintenance of such systems) at a voice efficiency of at least one voice path per 12.5 kHz of spectrum bandwidth until December 31, 2016.
- (3) The licensees designated in paragraph (d)(2) of this section must, no later than January 31, 2017, file a declaration through the Universal Licensing System that they are operating these channels at a voice efficiency of at least one voice path per 6.25 kHz of spectrum bandwidth.

[63 FR 58651, Nov. 2, 1998, as amended at 65 FR 53645, Sept. 5, 2000; 65 FR 66655, Nov. 7, 2000; 67 FR 76701, Dec. 13, 2002; 70 FR 21673, Apr. 27, 2005; 72 FR 48861, Aug. 24, 2007; 79 FR 71326, Dec. 2, 2014]

& Back to Top

§90.537 Trunking requirement.

- (a) General use and State License channels. All systems using six or more narrowband channels in the 769-775 MHz and 799-805 MHz frequency bands must be trunked systems, except for those described in paragraph (b) of this section.
- (b) Interoperability and low power channels. Trunking is permitted only on Interoperability channels specified in §90.531(b)(1)(iii). Trunked use must be strictly on a secondary, non-interference basis to conventional operations. The licensee must monitor and immediately release these channels when they are needed for interoperability purposes. All systems using narrowband low power channels listed in §90.531(b)(3) and (4) are exempt from the trunking requirements described in paragraph (a) of this section.

[79 FR 39340, July 10, 2014]

Back to Top

§90.539 Frequency stability.

Transmitters designed to operate in 769-775 MHz and 799-805 MHz frequency bands must meet the frequency stability requirements in this section.

(a) Mobile, portable and control transmitters must normally use automatic frequency control (AFC) to lock on to the base station signal.

- (b) The frequency stability of base transmitters operating in the narrowband segment must be 100 parts per billion or better.
- (c) The frequency stability of mobile, portable, and control transmitters operating in the narrowband segment must be 400 parts per billion or better when AFC is locked to the base station. When AFC is not locked to the base station, the frequency stability must be at least 1.0 ppm for 6.25 kHz, 1.5 ppm for 12.5 kHz (2 channel aggregate), and 2.5 ppm for 25 kHz (4 channel aggregate).
 - (d) The frequency stability of base transmitters operating in the wideband segment must be 1 part per million or better.
- (e) The frequency stability of mobile, portable and control transmitters operating in the wideband segment must be 1.25 parts per million or better when AFC is locked to a base station, and 5 parts per million or better when AFC is not locked.

[63 FR 58651, Nov. 2, 1998, as amended at 65 FR 53646, Sept. 5, 2000; 72 FR 48861, Aug. 24, 2007]

♣ Back to Top

§90.541 Transmitting power and antenna height limits.

The transmitting power and antenna height of base, mobile, portable and control stations operating in the 769-775 MHz and 799-805 MHz frequency bands must not exceed the maximum limits in this section. Power limits are listed in effective radiated power (ERP).

- (a) The transmitting power and antenna height of base stations must not exceed the limits given in paragraph (a) of §90.635.
- (b) The transmitting power of a control station must not exceed 200 watts ERP.
- (c) The transmitting power of a mobile unit must not exceed 100 watts ERP.
- (d) The transmitting power of a portable (hand-held) unit must not exceed 3 watts ERP.
- (e) Transmitters operating on the narrowband low power channels listed in §90.531(b)(3) and (4), must not exceed 2 watts ERP.

[79 FR 71326, Dec. 2, 2014]

♣ Back to Top

§90.542 Broadband transmitting power limits.

- (a) The following power limits apply to the 758-768/788-798 MHz band:
- (1) Fixed and base stations transmitting a signal in the 758-768 MHz band with an emission bandwidth of 1 MHz or less must not exceed an ERP of 1000 watts and an antenna height of 305 m HAAT, except that antenna heights greater than 305 m HAAT are permitted if power levels are reduced below 1000 watts ERP in accordance with Table 1 of this section.
- (2) Fixed and base stations located in a county with population density of 100 or fewer persons per square mile, based upon the most recently available population statistics from the Bureau of the Census, and transmitting a signal in the 758-768 MHz band with an emission bandwidth of 1 MHz or less must not exceed an ERP of 2000 watts and an antenna height of 305 m HAAT, except that antenna heights greater than 305 m HAAT are permitted if power levels are reduced below 2000 watts ERP in accordance with Table 2 of this section.
- (3) Fixed and base stations transmitting a signal in the 758-768 MHz band with an emission bandwidth greater than 1 MHz must not exceed an ERP of 1000 watts/MHz and an antenna height of 305 m HAAT, except that antenna heights greater than 305 m HAAT are permitted if power levels are reduced below 1000 watts/MHz ERP accordance with Table 3 of this section.
- (4) Fixed and base stations located in a county with population density of 100 or fewer persons per square mile, based upon the most recently available population statistics from the Bureau of the Census, and transmitting a signal in the 758-768 MHz band with an emission bandwidth greater than 1 MHz must not exceed an ERP of 2000 watts/MHz and an antenna height of 305 m HAAT, except that antenna heights greater than 305 m HAAT are permitted if power levels are reduced below 2000 watts/MHz ERP in accordance with Table 4 of this section.
- (5) Licensees of fixed or base stations transmitting a signal in the 758-768 MHz band at an ERP greater than 1000 watts must comply with the provisions set forth in paragraph (b) of this section.
 - (6) Control stations and mobile stations transmitting in the 758-768 MHz band and the 788-798 MHz band are limited to 30 watts ERP.
 - (7) Portable stations (hand-held devices) transmitting in the 758-768 MHz band and the 788-798 MHz band are limited to 3 watts ERP.
- (8) For transmissions in the 758-768 MHz and 788-798 MHz bands, licensees may employ equipment operating in compliance with either of the following measurement techniques:
- (i) The maximum composite transmit power shall be measured over any interval of continuous transmission using instrumentation calibrated in terms of RMS-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, etc., so as to obtain a true maximum composite measurement for the emission in question over the full bandwidth of the channel.
 - (ii) A Commission-approved average power technique.

TABLE 1 TO §90.542(a)—PERMISSIBLE POWER AND ANTENNA HEIGHTS FOR BASE AND FIXED STATIONS IN THE 758-768 MHz BAND TRANSMITTING A SIGNAL WITH AN EMISSION BANDWIDTH OF 1 MHz OR LESS

Antenna height (AAT) in meters (feet)	Effective radiated power (ERP) (watts)	
Above 1372 (4500)	65	
Above 1220 (4000) To 1372 (4500)	70	
Above 1067 (3500) To 1220 (4000)	75	
Above 915 (3000) To 1067 (3500)	100	

Above 763 (2500) To 915 (3000)	140
Above 610 (2000) To 763 (2500)	200
Above 458 (1500) To 610 (2000)	350
Above 305 (1000) To 458 (1500)	600
Up to 305 (1000)	1000

TABLE 2 TO §90.542(a)—PERMISSIBLE POWER AND ANTENNA HEIGHTS FOR BASE AND FIXED STATIONS IN THE 758-768 MHz BAND TRANSMITTING A SIGNAL WITH AN EMISSION BANDWIDTH OF 1 MHz OR LESS

Antenna height (AAT) in meters (feet)	Effective radiated power (ERP) (watts)	
Above 1372 (4500)	1	
Above 1220 (4000) To 1372 (4500)	140	
Above 1067 (3500) To 1220 (4000)	150	
Above 915 (3000) To 1067 (3500)	200	
Above 763 (2500) To 915 (3000)	280	
Above 610 (2000) To 763 (2500)	400	
Above 458 (1500) To 610 (2000)	700	
Above 305 (1000) To 458 (1500)	1200	
Up to 305 (1000)	2000	

TABLE 3 TO §90.542(a)—PERMISSIBLE POWER AND ANTENNA HEIGHTS FOR BASE AND FIXED STATIONS IN THE 758-768 MHZ BAND TRANSMITTING A SIGNAL WITH AN EMISSION BANDWIDTH GREATER THAN 1 MHZ

Antenna height (AAT) in meters (feet)	Effective radiated power (ERP) per MHz (watts/MHz)
Above 1372 (4500)	65
Above 1220 (4000) To 1372 (4500)	70
Above 1067 (3500) To 1220 (4000)	75
Above 915 (3000) To 1067 (3500)	100
Above 763 (2500) To 915 (3000)	140
Above 610 (2000) To 763 (2500)	200
Above 458 (1500) To 610 (2000)	350
Above 305 (1000) To 458 (1500)	600
Up to 305 (1000)	1000

TABLE 4 TO §90.542(a)—PERMISSIBLE POWER AND ANTENNA HEIGHTS FOR BASE AND FIXED STATIONS IN THE 758-768 MHz BAND TRANSMITTING A SIGNAL WITH AN EMISSION BANDWIDTH GREATER THAN 1 MHz

Antenna height (AAT) in meters (feet)	Effective radiated power (ERP) per MHz (watts/MHz)
Above 1372 (4500)	130
Above 1220 (4000) To 1372 (4500)	140
Above 1067 (3500) To 1220 (4000)	150
Above 915 (3000) To 1067 (3500)	200
Above 763 (2500) To 915 (3000)	280
Above 610 (2000) To 763 (2500)	400
Above 458 (1500) To 610 (2000)	700
Above 305 (1000) To 458 (1500)	1200
Up to 305 (1000)	2000

(b) For base and fixed stations operating in the 758-768 MHz band in accordance with the provisions of paragraph (a)(5) of this section, the power flux density that would be produced by such stations through a combination of antenna height and vertical gain pattern must not exceed 3000 microwatts per square meter on the ground over the area extending to 1 km from the base of the antenna mounting structure.

[72 FR 48861, Aug. 24, 2007, as amended at 79 FR 600, Jan. 6, 2014]

& Back to Top

§90.543 Emission limitations.

Transmitters designed to operate in 769-775 MHz and 799-805 MHz frequency bands must meet the emission limitations in paragraphs (a) through (d) of this section. Class A and Class B signal boosters retransmitting signals in the 769-775 MHz and 799-805 MHz frequency bands are exempt from the limits listed in paragraph (a) of this section when simultaneously retransmitting multiple signals and instead shall be subject to the limit listed in paragraph (c) of this section when operating in this manner. Transmitters operating in 758-768 MHz and 788-798 MHz bands must meet the emission limitations in (e) of this section.

(a) The adjacent channel power (ACP) requirements for transmitters designed for various channel sizes are shown in the following tables. Mobile station requirements apply to handheld, car mounted and control station units. The tables specify a value for the ACP as a function of the displacement from the channel center frequency and measurement bandwidth. In the following tables, "(s)" indicates a swept measurement may be used.

6.25 KHZ MOBILE TRANSMITTER ACP REQUIREMENTS

Offset from center frequency (kHz)	Measurement bandwidth (kHz)	Maximum ACP relative (dBc)
6.25	6.25	-40
12.5	6.25	-60
18.75	6.25	-60
25.00	6.25	-65
37.50	25.00	-65
62.50	25.00	-65
87.50	25.00	-65
150.00	100.00	-65
250.00	100.00	-65
350.00	100.00	-65
>400 kHz to 12 MHz	30 (s)	-75
12 MHz to paired receive band	30 (s)	-75
In the paired receive band	30 (s)	-100

12.5 KHZ MOBILE TRANSMITTER ACP REQUIREMENTS

Offset from center frequency (kHz)	Measurement bandwidth (kHz)	Maximum ACP relative (dBc)
9.375	6.25	-40
15.625	6.25	-60
21.875	6.25	-60
37.50	25.00	-60
62.50	25.00	-65
87.50	25.00	-65
150.00	100	-65
250.00	100	-65
350.00	100	-65
>400 to 12 MHz	30 (s)	-75
12 MHz to paired receive band	30 (s)	-75
In the paired receive band	30 (s)	-100

25 KHZ MOBILE TRANSMITTER ACP REQUIREMENTS

Offset from center frequency (kHz)	Measurement bandwidth (kHz)	Maximum ACP relative (dBc)
15.625	6.25	-40
21.875	6.25	-60
37.50	25	-60
62.50	25	-65
87.50	25	-65
150.00	100	-65
250.00	100	-65
350.00	100	-65
>400 kHz to 12 MHz	30 (s)	-75
12 MHz to paired receive band	30 (s)	-75
In the paired receive band	30 (s)	-100

6.25 KHZ BASE TRANSMITTER ACP REQUIREMENTS

Offset from center frequency (kHz)	Measurement bandwidth (kHz)	Maximum ACP (dBc)
6.25	6.25	-40
12.50	6.25	-60
18.75	6.25	-60
25.00	6.25	-65
37.50	25	-65
62.50	25	-65
87.50	25	-65
150.00	100	-65
250.00	100	-65
350.00	100	-65
>400 to 12 MHz	30 (s)	-80

12 MHz to paired receive band	30 (s)	-80
In the paired receive band	30 (s)	¹ -85

¹Although we permit individual base transmitters to radiate a maximum ACP of -85 dBc in the paired receive band, licensees deploying these transmitters may not exceed an ACP of -100 dBc in the paired receive band when measured at either the transmitting antenna input port or the output of the transmitter combining network. Consequently, licensees deploying these transmitters may need to use external filters to comply with the more restrictive ACP limit.

12.5 KHZ BASE TRANSMITTER ACP REQUIREMENTS

Offset from center frequency (kHz)	Measurement bandwidth (kHz)	Maximum ACP (dBc)
9.375	6.25	-40
15.625	6.25	-60
21.875	6.25	-60
37.5	25	-60
62.5	25	-65
87.5	25	-65
150	100	-65
250	100	-65
350.00	100	-65
>400 kHz to 12 MHz	30 (s)	-80
12 MHz to paired receive band	30 (s)	-80
In the paired receive band	30 (s)	¹ -85

¹Although we permit individual base transmitters to radiate a maximum ACP of -85 dBc in the paired receive band, licensees deploying these transmitters may not exceed an ACP of -100 dBc in the paired receive band when measured at either the transmitting antenna input port or the output of the transmitter combining network. Consequently, licensees deploying these transmitters may need to use external filters to comply with the more restrictive ACP limit.

25 KHZ BASE TRANSMITTER ACP REQUIREMENTS

Offset from center frequency (kHz)	Measurement bandwidth (kHz)	Maximum ACP (dBc)
15.625	6.25	-40
21.875	6.25	-60
37.5	25	-60
62.5	25	-65
87.5	25	-65
150	100	-65
250	100	-65
350	100.00	-65
>400 kHz to 12 MHz	30 (s)	-80
12 MHz to paired receive band	30 (s)	-80
In the paired receive band	30 (s)	1-85

¹Although we permit individual base transmitters to radiate a maximum ACP of -85 dBc in the paired receive band, licensees deploying these transmitters may not exceed an ACP of -100 dBc in the paired receive band when measured at either the transmitting antenna input port or the output of the transmitter combining network. Consequently, licensees deploying these transmitters may need to use external filters to comply with the more restrictive ACP limit.

- (b) ACP measurement procedure. The following are the procedures for making the transmitter ACP measurements. For all measurements modulate the transmitter as it would be modulated in normal operating conditions. For time division multiple access (TDMA) systems, the measurements are to be made under TDMA operation only during time slots when the transmitter is active. All measurements are made at the transmitter's output port. If a transmitter has an integral antenna, a suitable power coupling device shall be used to couple the RF signal to the measurement instrument. The coupling device shall substantially maintain the proper transmitter load impedance. The ACP measurements may be made with a spectrum analyzer capable of making direct ACP measurements. "Measurement bandwidth", as used for non-swept measurements, implies an instrument that measures the power in many narrow bandwidths equal to the nominal resolution bandwidth and integrates these powers to determine the total power in the specified measurement bandwidth.
- (1) Setting reference level. Set transmitter to maximum output power. Using a spectrum analyzer capable of ACP measurements, set the measurement bandwidth to the channel size. For example, for a 6.25 kHz transmitter set the measurement bandwidth to 6.25 kHz. Set the frequency offset of the measurement bandwidth to zero and adjust the center frequency of the instrument to the assigned center frequency to measure the average power level of the transmitter. Record this power level in dBm as the "reference power level."
- (2) Non-swept power measurement. Using a spectrum analyzer capable of ACP measurements, set the mesurement bandwidth and frequency offset from the assigned center frequency as shown in the tables in §90.543 (a) above. Any value of resolution bandwidth may be used as long as it does not exceed 2 percent of the specified measurement bandwidth. Measure the power level in dBm. These measurements should be made at maximum power. Calculate ACP by substracting the reference power level measured in (b)(1) from the measurements made in this step. The absolute value of the calculated ACP must be greater than or equal to the absolute value of the ACP given in the table for each condition above.

- (3) Swept power measurement. Set a spectrum analyzer to 30 kHz resolution bandwidth, 1 MHz video bandwidth and average, sample, or RMS detection. Set the reference level of the spectrum analyzer to the RMS value of the transmitter power. Sweep above and below the carrier frequency to the limits defined in the tables. Calculate ACP by substracting the reference power level measured in (b)(1) from the measurements made in this step. The absolute value of the calculated ACP must be greater than or equal to the absolute value of the ACP given in the table for each condition above.
- (c) Out-of-band emission limit. On any frequency outside of the frequency ranges covered by the ACP tables in this section, the power of any emission must be reduced below the mean output power (P) by at least 43 + 10log (P) dB measured in a 100 kHz bandwidth for frequencies less than 1 GHz, and in a 1 MHz bandwidth for frequencies greater than 1 GHz.
- (d) Authorized bandwidth. Provided that the ACP requirements of this section are met, applicants may request any authorized bandwidth that does not exceed the channel size.
- (e) For operations in the 758-768 MHz and the 788-798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the
- (1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment,
- (2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.
 - (3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB.
- (4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.
- (5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.
- (f) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.
- (g) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

[70 FR 21666, Apr. 27, 2005, as amended at 72 FR 48862, Aug. 24, 2007; 79 FR 600, Jan. 6, 2014; 79 FR 39340, July 10, 2014; 79 FR 71326, Dec. 2, 2014]

& Back to Top

§90.547 Narrowband Interoperability channel capability requirement.

- (a) Except as noted in this section, mobile and portable transmitters operating on narrowband channels in the 769-775 MHz and 799-805 MHz frequency bands must be capable of being programmed to operate on all of the designated nationwide narrowband Interoperability channels pursuant to the standards specified in this part.
- (1) Mobile and portable transmitters that are designed to operate only on the Low Power Channels specified in §90.531 (b)(3) and (4) are exempt from this Interoperability channel requirement.
- (2) Mobile and portable transmitters that are designed to operate only in the data mode must be capable of operation on the data Interoperability channels specified in §90.531(b)(1)(i); but need not be capable of voice operation on other Interoperability channels.
- (3) Mobile and portable transmitters that are designed to operate only in the voice mode do not have to operate on the data Interoperability channels specified in §90.531(b)(1)(i).
 - (b) Mobile and portable transmitters designed for data are not required to be voice capable, and vice versa.

[67 FR 61005, Sept. 27, 2002, as amended at 72 FR 48863, Aug. 24, 2007; 79 FR 71326, Dec. 2, 2014]

♣ Back to Top

§90.548 Interoperability Technical Standards.

- (a) Transmitters designed after August 11, 2014 to operate on the narrowband interoperability achannels in the 769-775 and 799-805 MHz band (see §90.531) shall conform to the following technical standards (transmitters certified prior to this date are grandfathered):
- (1) Transmitters designed for voice operation shall include a 12.5 kilohertz bandwidth mode of operation conforming to the following standards: ANSI/TIA-102.BAAA-A-2003 and ANSI/TIA-102.BABA-2003.
- (2) Transmitters designed for data transmission shall include a 12.5 kilohertz bandwidth mode of operation conforming to the following standards: ANSI/TIA-102.BAEA-B-2012, ANSI/TIA-102.BAAA-A-2003, ANSI/TIA-102.BAEB-A-2005, and ANSI/TIA-102.BAEE-B-2010.
- (b) The Director of the Federal Register approves these incorporations by reference in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. Material incorporated by reference may be inspected at the Federal Communications Commission, 445 12th Street SW., Washington, DC (Reference Information Center) [202-418-0270] or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go to: http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html.

- (1) TIA/EIA, 2500 Wilson Boulevard, Arlington, VA 22201 703-907-7974. These standards are also available from Global Engineering Documents, 15 Inverness Way East, Englewood, CO 80112; or the American National Standards Institute, 25 West 43rd Street, Fourth Floor, New York, NY 10036, www.ansi.org.
 - (i) ANSI/TIA-102.BAAA-A-2003, Project 25 FDMA-Common Air Interface, approved September 2003.
 - (ii) ANSI/TIA-102.BABA-2003, Project 25 Vocoder Description, approved December 2003.
- (iii) ANSI/TIA-102.BAEA-B-2012, Project 25 Data Overview—New Technology Standards Project—Digital Radio Technical Standards, approved June 2012.
- (iv) ANSI/TIA-102.BAEB-A-2005, Project 25 Packet Data Specification—New Technology Standards Project—Digital Radio Technical Standards, approved March 2005.
- (v) ANSI/TIA-102.BAEE-B-2010, Project 25 Radio Management Protocols—New Technology Standards Project—Digital Radio Technical Standards, approved May 2010.
 - (2) [Reserved]
 - (c) Equipment certified by the P25 Compliance Assessment Program is presumed to comply with this section.

[79 FR 39340, July 10, 2014, as amended at 79 FR 71326, Dec. 2, 2014]

& Back to Top

§90.549 Transmitter certification.

Transmitters operated in the 758-775 MHz and 788-805 MHz frequency bands must be of a type that have been authorized by the Commission under its certification procedure as required by §90.203.

[79 FR 600, Jan. 6, 2014]

& Back to Top

§90.551 Construction requirements.

Each station authorized under this subpart to operate in the 769-775 MHz and 799-805 MHz frequency bands must be constructed and placed into operation within 12 months from the date of grant of the authorization, except for State channels. However, licensees may request a longer construction period, up to but not exceeding 5 years, pursuant to §90.155(b). State channels are subject to the build-out requirements in §90.529.

[72 FR 48863, Aug. 24, 2007]

& Back to Top

§90.553 Encryption.

- (a) Encryption is permitted on all but the two nationwide Interoperability calling channels. Radios employing encryption must have a readily accessible switch or other readily accessible control that permits the radio user to disable encryption.
- (b) If encryption is employed, then transmitters manufactured after August 11, 2014 must use the Advanced Encryption Standard (AES) specified in ANSI/TIA-102.AAAD-A: Project 25 Digital Land Mobile Radio-Block Encryption Protocol, approved August 20, 2009 Until 2030, manufacturers may also include the Digital Encryption Standard (DES) or Triple Data Encryption Algorithm (TDEA), in addition to but not in place of AES, for compatibility with legacy radios that lack AES capability. The Director of the Federal Register approves this incorporation by reference in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. The standard can also be purchased from TIA/EIA, 2500 Wilson Boulevard, Arlington, VA 22201 703-907-7974; Global Engineering Documents, 15 Inverness Way East, Englewood, CO 80112; or the American National Standards Institute, 25 West 43rd Street, Fourth Floor, New York, NY 10036, www.ansi.org. Material incorporated by reference may be inspected at the Federal Communications Commission, 445 12th Street SW., Washington, DC (Reference Information Center) 202-418-0270 or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go to: http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html.
- (c) The Director of the Federal Register approves this incorporation by reference in accordance with 5 U.S.C. 552(a) and 1 CFR part 51. Copies of the standard listed in this section that are incorporated by reference may be inspected at the Federal Communications Commission, 445 12th Street, SW., Washington, DC (Reference Information Center) or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go to: http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html. The standard can also be purchased from TIA/EIA, 2500 Wilson Boulevard, Arlington, VA, 22201; Global Engineering Documents, 15 Inverness Way East, Englewood, CO 80112; or the American National Standards Institute, 25 West 43rd Street, Fourth Floor, New York, NY 10036 (or via the Internet at www.ansi.org.)

[66 FR 10636, Feb. 16, 2001, as amended at 67 FR 61006, Sept. 26, 2002; 79 FR 39341, July 10, 2014]

& Back to Top

§90.555 Information exchange.

- (a) Prior notification. Public safety licensees authorized to operate in the 758-775 MHz and 788-805 MHz bands may notify any licensee authorized to operate in the 746-757 MHz or 776-787 MHz bands that they wish to receive prior notification of the activation or modification of the licensee's base or fixed stations in their area. Thereafter, the 746-757 MHz or 776-787 MHz band licensee must provide the following information to the public safety licensee at least 10 business days before a new base or fixed station is activated or an existing base or fixed station is modified:
 - (1) Location;
 - (2) Effective radiated power;

- (3) Antenna height; and
- (4) Channels available for use.
- (b) Purpose of prior notification. The prior coordination of base or fixed stations is for informational purposes only. Public safety licensees are not afforded the right to accept or reject the activation of a proposed base or fixed station or to unilaterally require changes in its operating parameters. The principal purposes of notification are to:
- (1) Allow a public safety licensee to advise the 746-757 or 776-787 MHz band licensee whether it believes a proposed base or fixed station will generate unacceptable interference;
- (2) Permit 746-757 and 776-787 MHz band licensees to make voluntary changes in base or fixed station parameters when a public safety licensee alerts them to possible interference; and,
 - (3) Rapidly identify the source if interference is encountered when the base or fixed station is activated.
- (c) Public Safety Information Exchange. (1) Upon request by a 746-757 or 776-787 MHz band licensee, public safety licensees authorized to operate radio systems in the 758-775 and 788-805 MHz bands shall provide the operating parameters of their radio system to the 746-757 or 776-787 MHz band licensee.
- (2) Public safety licensees who perform the information exchange described in this section must notify the appropriate 746-757 or 776-787 MHz band licensees prior to any technical changes to their radio system.

[72 FR 27713, May 16, 2007, as amended at 72 FR 67578, Nov. 29, 2007; 79 FR 601, Jan. 6, 2014]

& Back to Top

§90.557 Secondary fixed signaling operations.

Trunked and conventional 700 MHz narrowband systems may conduct fixed ancillary signaling and data transmissions subject to the following requirements:

- (a) Operations are permitted only on:
- (1) Narrowband State License channels specified in §90.531(b)(5), subject to the discretion of the relevant State licensee; and
- (2) Narrowband General Use channels specified in §90.531(b)(6), subject to the discretion of the regional planning committee.
- (b) All operations must be on a secondary, non-interference basis to the primary mobile operation of any other licensee.
- (c) The output power at the remote site must not exceed 30 watts.
- (d) Automatic means must be provided to deactivate the remote transmitter in the event the carrier remains on for a period in excess of three minutes.
 - (e) Operational fixed stations authorized pursuant to this section are exempt from the requirements of §§90.425, 90.429, and 90.559.
- (f) Any operations undertaken in a shared use environment must be conducted pursuant to an agreement between the licensee and each participant, as set forth in §90.179.

[79 FR 39341, July 10, 2014]

& Back to Top

§90.559 Station Identification.

- (a) Conventional systems of communication shall be identified in accordance with existing regulations governing such matters.
- (b) Trunked systems of communication, except as noted in paragraph (c) of this section, shall be identified through the use of an automatic device which transmits the call sign of the base station facility at 30 minute intervals. Such station identification shall be made on the lowest frequency in the base station trunk group assigned the licensee. Should this frequency be in use at the time station identification is required, such identification may be made at the termination of the communication in progress on this frequency. Identification may be made by voice or International Morse Code. When the call sign is transmitted in International Morse Code, it must be at a rate of between 15 to 20 words per minute and by means of tone modulation of the transmitter, the tone frequency being between 800 and 1000 hertz.
- (c) Stations operating in the 769-775/799-805 MHz band that are licensed on an exclusive basis, and normally employ digital signals for the transmission of data, text, control codes, or digitized voice may also be identified by digital transmission of the call sign. A licensee that identifies its station in this manner must provide the Commission, upon its request, information sufficient to decode the digital transmission and ascertain the call sign transmitted.

[79 FR 39341, July 10, 2014]

♣ Back to Top

Need assistance?

Appendix L Region 19 - New England Channel Allotment

Ö	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Connecticut	-	-	-	-	-	-	-	77.0	-	-	-	-
33	-	-	-																											
-																			 											
3				-																										

		FCC Channel	Base	Mobile
County	Band	Number	Frequency	Frequency
Notation				
	min out annua arannaa		ATTACANA ANTANA ATTACAN	
Fairfield	Voice 12.5KHz	85-86	769.531250	799.531250
	Voice 12.5KHz	173-174	770.081250	800.081250
	Voice 12.5KHz	253-254	770.581250	800.581250
¥	Voice 12.5KHz	357-358	771.231250	801.231250
	Voice 12.5KHz	405-406	771.531250	801.531250
	Voice 12.5KHz	445-446	771.781250	801.781250
	Voice 12.5KHz	793-794	773.956250	803.956250
	Voice 12.5KHz	833-834	774.206250	804.206250
Hartford	Voice 12.5KHz	41-42	769.256250	799.256250
	Voice 12.5KHz	81-82	769.506250	799.506250
	Voice 12.5KHz	121-122	769.756250	799.756250
	Voice 12.5KHz	201-202	770.256250	800.256250
	Voice 12.5KHz	297-298	770.856250	800.856250
	Voice 12.5KHz	369-370	771.306250	801.306250
	Voice 12.5KHz	409-410	771.556250	801.556250
	Voice 12.5KHz	449-450	771.806250	801.806250
	Voice 12.5KHz	501-502	772.131250	802.131250
	Voice 12.5KHz	541-542	772.381250	802.381250
	Voice 12.5KHz	589-590	772.681250	802.681250
	Voice 12.5KHz	629-630	772.931250	802.931250
	Voice 12.5KHz	673-674	773.206250	803.206250
	Voice 12.5KHz	719-720	773.493750	803.493750
	Voice 12.5KHz	797-798	773.981250	803.981250
	Voice 12.5KHz	837-838	774.231250	804.231250
	Voice 12.5KHz	905-906	774.656250	804.656250
	Voice 12.5KHz	945-946	774.906250	804.906250
Litchfield	Voice 12.5KHz	207-208	770.293750	800.293750
PICCULIEIG	Voice 12.5KHz	429-430	771.681250	801.681250
	Voice 12.5KHz	469-470	771.031250	801.931250
	Voice 12.5KHz	561-562	772.506250	802.506250
	Voice 12.5KHz	621-622	772.881250	802.881250
	Voice 12.5KHz	781-782	773.881250	803.881250
	Voice 12.5KHz	879-880	774.493750	804.493750
Middlesex	Voice 12.5KHz	47-48	769.293750	799.293750
	Voice 12.5KHz	89-90	769.556250	799.556250
	Voice 12.5KHz	129-130	769.806250	799.806250
	Voice 12.5KHz	177-178	770.106250	800.106250
	Voice 12.5KHz	285-286	770.781250	800.781250

	Voice 12.5KHz Voice 12.5KHz	343-344 389-390 441-442 481-482 533-534 609-610 667-668 709-710 759-760 869-870	771.143750 771.431250 771.756250 772.006250 772.331250 772.806250 773.168750 773.431250 773.743750 774.431250	801.143750 801.431250 801.756250 802.006250 802.331250 802.806250 803.168750 803.431250 803.743750 804.431250
New Haven	Voice 12.5KHz	13-14 53-54 93-94 213-214 259-260 329-330 377-378 417-418 461-462 507-508 549-550 597-598 637-638 713-714 753-754 821-822 865-866 919-920	769.081250 769.331250 769.581250 770.331250 770.618750 771.056250 771.356250 771.881250 772.168750 772.431250 772.731250 772.981250 773.456250 773.706250 774.131250 774.406250 774.743750	799.081250 799.331250 799.581250 800.331250 800.618750 801.056250 801.356250 801.606250 801.881250 802.168750 802.431250 802.731250 802.981250 803.456250 803.706250 804.131250 804.743750
New London	Voice 12.5KHz	59-60 99-100 161-162 219-220 349-350 425-426 517-518 577-578 617-618 661-662 705-706 789-790 873-874	769.368750 769.618750 770.006250 770.368750 771.181250 771.656250 772.231250 772.606250 772.856250 773.131250 773.406250 773.931250 774.456250	799.368750 799.618750 800.006250 800.368750 801.181250 801.656250 802.231250 802.606250 802.856250 803.131250 803.406250 803.931250 804.456250
Tolland	Voice 12.5KHz	55-56 95-96 171-172 253-254 357-358 401-402 489-490 553-554 601-602 715-716 755-756 863-864	769.343750 769.593750 770.068750 770.581250 771.231250 771.506250 772.056250 772.456250 772.756250 773.468750 773.718750 774.393750	799.343750 799.593750 800.068750 800.581250 801.231250 801.506250 802.056250 802.456250 802.756250 803.468750 803.718750 804.393750

Part 2, Appendix L

Windham	Voice 12.5KHz	83-84	769.518750	799.518750
YI Z Z Z GCZ Z GCZ	Voice 12.5KHz	139-140	769.868750	799.868750
	Voice 12.5KHz	331-332	771.068750	801.068750
	Voice 12.5KHz	385-386	771.406250	801.406250
	Voice 12.5KHz	445-446	771.781250	801.781250
	Voice 12.5KHz	505-506	772.156250	802.156250
	Voice 12.5KHz	547-548	772.418750	802.418750
	Voice 12.5KHz	593-594	772.706250	802.706250
	Voice 12.5KHz	633-634	772.956250	802.956250
	Voice 12.5KHz	793-794	773.956250	803.956250
	Voice 12.5KHz	839-840	774.243750	804.243750
	Voice 12.5KHz	901-902	774.631250	804.631250
	Voice 12 5KHz	941-942	774.881250	804.881250

_	-	_	-	-	-	-	-	-	-	-	_	-	-	-	-	Massachusetts	-	-	-	-	-	-	-	-	770	-	-	-

		FCC Channel	Base	Mobile
County	Band	Number	Frequency	Frequency
Notation				
Barnstable	Voice 12.5KHz	57-58	769.356250	799.356250
	Voice 12.5KHz	125-126	769.781250	799.781250
	Voice 12.5KHz	165-166	770.031250	800.031250
	Voice 12.5KHz	213-214	770.331250	800.331250
	Voice 12.5KHz	253-254	770.581250	800.581250
	Voice 12.5KHz	297-298	770.856250	800.856250
	Voice 12.5KHz	337-338	771.106250	801.106250
	Voice 12.5KHz	377-378	771.356250	801.356250
	Voice 12.5KHz	433-434	771.706250	801.706250
	Voice 12.5KHz	477-478	771.981250	801.981250
	Voice 12.5KHz	541-542	772.381250	802.381250
	Voice 12.5KHz	617-618	772.856250	802.856250
	Voice 12.5KHz	661-662	773.131250	803.131250
	Voice 12.5KHz	713-714	773.456250	803.456250
	Voice 12.5KHz	785-786	773.906250	803.906250
	Voice 12.5KHz	829-830	774.181250	804.181250
	Voice 12.5KHz	877-878	774.481250	804.481250
	Voice 12.5KHz	917-918	774.731250	804.731250
		450 450	770 05000	200 255250
Berkshire	Voice 12.5KHz	169-170	770.056250	800.056250
	Voice 12.5KHz	249-250	770.556250	800.556250
	Voice 12.5KHz	381-382	771.381250	801.381250
	Voice 12.5KHz	437-438	771.731250 772.206250	801.731250 802.206250
	Voice 12.5KHz Voice 12.5KHz	513-514 581-582	772.206250	802.206250
	Voice 12.5KHz	705-706	773.406250	803.406250
	Voice 12.5KHz	787-788	773.400250	803.918750
	Voice 12.5KHz	861-862	774.381250	804.381250
	VOICE 12.JRHZ	001-002	774.501250	004.501250
Bristol	Voice 12.5KHz	53-54	769.331250	799.331250
	Voice 12.5KHz	129-130	769.806250	799.806250
	Voice 12.5KHz	173-174	770.081250	800.081250
	Voice 12.5KHz	285-286	770.781250	800.781250
	Voice 12.5KHz	381-382	771.381250	801.381250
	Voice 12.5KHz	429-430	771.681250	801.681250
	Voice 12.5KHz	473-474	771.956250	801.956250
	Voice 12.5KHz	545-546	772.406250	802.406250
	Voice 12.5KHz	613-614	772.831250	802.831250
	Voice 12.5KHz	669-670	773.181250	803.181250
	Voice 12.5KHz	717-718	773.481250	803.481250
	Voice 12.5KHz	781-782	773.881250	803.881250
	Voice 12.5KHz	869-870	774.431250	804.431250
	Voice 12.5KHz	915-916	774.718750	804.718750

Dukes	Voice 12.5KHz	41-42	769.256250	799.256250
	Voice 12.5KHz	97-98	769.606250	799.606250
	Voice 12.5KHz	137-138	769.856250	799.856250
	Voice 12.5KHz	177-178	770.106250	800.106250
	Voice 12.5KHz	241-242	770.506250	800.506250
	Voice 12.5KHz	289-290	770.806250	800.806250
	Voice 12.5KHz			
		345-346	771.156250	801.156250
	Voice 12.5KHz	393-394	771.456250	801.456250
	Voice 12.5KHz	465-466	771.906250	801.906250
	Voice 12.5KHz	533-534	772.331250	802.331250
	Voice 12.5KHz	585-586	772.656250	802.656250
	Voice 12.5KHz	633-634	772.956250	802.956250
	Voice 12.5KHz	701-702	773.381250	803.381250
	Voice 12.5KHz	757-758	773.731250	803.731250
	Voice 12.5KHz	797-798	773.981250	803.981250
	Voice 12.5KHz	837-838	774.231250	804.231250
	Voice 12.5KHz	905-906	774.656250	804.656250
	Voice 12.5KHz	945-946	774.906250	804.906250
	VOICE 12.3KHZ	343-340	114.900230	804.900230
Essex	Voice 12.5KHz	41-42	769.256250	799.256250
1,100001	Voice 12.5KHz	81-82	769.506250	799.506250
	Voice 12.5KHz	121-122	769.756250	799.756250
	Voice 12.5KHz	161-162	770.006250	800.006250
	Voice 12.5KHz	205-206	770.281250	800.281250
	Voice 12.5KHz	253-254	770.581250	800.581250
	Voice 12.5KHz	361-362	771.256250	801.256250
	Voice 12.5KHz	425-426	771.656250	801.656250
	Voice 12.5KHz	501-502	772.131250	802.131250
	Voice 12.5KHz	541-542	772.381250	802.381250
	Voice 12.5KHz	601-602	772.756250	802.756250
	Voice 12.5KHz	719-720	773.493750	803.493750
	Voice 12.5KHz	759-760	773.743750	803.743750
	Voice 12.5KHz	821-822	774.131250	804.131250
	Voice 12.5KHz	873-874	774.456250	804.456250
	Voice 12.5KHz	913-914	774.436250	804.706250
	VOICE 12.JKHZ	313-314	774.700230	804.706230
Franklin	Voice 12.5KHz	217-218	770.356250	800.356250
	Voice 12.5KHz	333-334	771.081250	801.081250
	Voice 12.5KHz	413-414	771.581250	801.581250
	Voice 12.5KHz	483-484	772.018750	802.018750
	Voice 12.5KHz	565-566	772.531250	802.531250
	Voice 12.5KHz	631-632	772.943750	802.943750
	Voice 12.5KHz	943-944	774.893750	804.893750
**	17 1 10 5	47 46	750 405050	E00 4050E0
Hampden	Voice 12.5KHz	17-18	769.106250	799.106250
	Voice 12.5KHz	91-92	769.568750	799.568750
	Voice 12.5KHz	133-134	769.831250	799.831250
	Voice 12.5KHz	175-176	770.093750	800.093750
	Voice 12.5KHz	245-246	770.531250	800.531250
	Voice 12.5KHz	289-290	770.806250	800.806250
	Voice 12.5KHz	345-346	771.156250	801.156250
	Voice 12.5KHz	393-394	771.456250	801.456250
	Voice 12.5KHz	457-458	771.856250	801.856250
	Voice 12.5KHz	521-522	772.256250	802.256250
	Voice 12.5KHz	573-574	772.581250	802.581250
	Voice 12.5KHz	613-614	772.831250	802.831250
	Voice 12.5KHz	665-666	773.156250	
	VOICE IZ. SKMZ	000-000	113.130230	803.156250

	Voice 12.5	KHz	711-712	773.443750	803.443750
	Voice 12.5	KHZ	751-752	773.693750	803.693750
	Voice 12.5		831-832	774.193750	804.193750
	Voice 12.5		871-872	774.443750	804.443750
	Voice 12.5				
	Voice 12.5	KHZ	913-914	774.706250	804.706250
Hampshire	Voice 12.5	KHz	45-46	769.281250	799.281250
	Voice 12.5		85-86	769.531250	799.531250
	Voice 12.5		203-204	770.268750	800.268750
	Voice 12.5		257-258	770.606250	800.606250
	Voice 12.5			770.868750	
			299-300		800.868750
	Voice 12.5		373-374	771.331250	801.331250
	Voice 12.5		465-466	771.906250	801.906250
	Voice 12.5		509-510	772.181250	802.181250
	Voice 12.5		557-558	772.481250	802.481250
	Voice 12.5	KHZ	605-606	772.781250	802.781250
	Voice 12.5	KHZ	675-676	773.218750	803.218750
	Voice 12.5	KHZ	717-718	773.481250	803.481250
	Voice 12.5	KHz	757-758	773.731250	803.731250
	Voice 12.5		835-836	774.218750	804.218750
	Voice 12.5		907-908	774.668750	804.668750
	Voice 12.5		947-948	774.918750	804.918750
	VOICE 12.2	MIL	241-240	774.510750	004.510750
Middlesex	Voice 12.5	KHZ	13-14	769.081250	799.081250
	Voice 12.5	KHz	57-58	769.356250	799.356250
	Voice 12.5		97-98	769.606250	799.606250
	Voice 12.5		137-138	769.856250	799.856250
	Voice 12.5		177-178	770.106250	800.106250
	Voice 12.5		241-242	770.506250	800.506250
	Voice 12.5		297-298	770.856250	800.856250
	Voice 12.5		337-338		
				771.106250	801.106250
	Voice 12.5		377-378	771.356250	801.356250
	Voice 12.5		441-442	771.756250	801.756250
	Voice 12.5		481-482	772.006250	802.006250
	Voice 12.5		525-526	772.281250	802.281250
	Voice 12.5		577-578	772.606250	802.606250
	Voice 12.5	KHZ	617-618	772.856250	802.856250
	Voice 12.5	KHZ	661-662	773.131250	803.131250
	Voice 12.5	KHz	709-710	773.431250	803.431250
	Voice 12.5	KHZ	749-750	773.681250	803.681250
	Voice 12.5	KHZ	789-790	773.931250	803.931250
	Voice 12.5	KHZ	865-866	774.406250	804.406250
	Voice 12.5		905-906	774.656250	804.656250
	Voice 12.5		945-946	774.906250	804.906250
Nantucket	Voice 12.5		13-14	769.081250	799.081250
	Voice 12.5	KHz	89-90	769.556250	799.556250
	Voice 12.5	KHz	133-134	769.831250	799.831250
	Voice 12.5	KHZ	173-174	770.081250	800.081250
	Voice 12.5	KHz	217-218	770.356250	800.356250
	Voice 12.5		281-282	770.756250	800.756250
	Voice 12.5		321-322	771.006250	801.006250
	Voice 12.5		361-362	771.256250	801.256250
	Voice 12.5		421-422	771.631250	801.631250
	Voice 12.5		473-474	771.956250	801.956250
	Voice 12.5		525-526	772.281250	802.281250
	Voice 12.5				
	voice 12.5	MIZ	577-578	772.606250	802.606250

	Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz	637-638 677-678 741-742 781-782 825-826 869-870 913-914	772.981250 773.231250 773.631250 773.881250 774.156250 774.431250 774.706250	802.981250 803.231250 803.631250 803.881250 804.156250 804.431250 804.706250
Norfolk	Voice 12.5KHz	43-44 85-86 217-218 257-258 329-330 371-372 413-414 465-466 513-514 557-558 605-606 757-758 797-798 837-838	769.268750 769.531250 770.356250 770.606250 771.056250 771.318750 771.581250 771.906250 772.206250 772.481250 772.781250 773.731250 773.981250 774.231250	799.268750 799.531250 800.356250 800.606250 801.056250 801.318750 801.581250 801.906250 802.206250 802.481250 802.781250 803.731250 803.981250 804.231250
Plymouth	Voice 12.5KHz	17-18 99-100 139-140 201-202 245-246 357-358 399-400 445-446 521-522 597-598 665-666 705-706 745-746 791-792 901-902 941-942	769.106250 769.618750 769.868750 770.256250 770.531250 771.231250 771.493750 771.781250 772.256250 772.731250 773.156250 773.406250 773.656250 773.943750 774.631250 774.881250	799.106250 799.618750 799.868750 800.256250 800.531250 801.231250 801.781250 802.256250 802.731250 803.156250 803.406250 803.656250 803.943750 804.631250 804.881250
Suffolk	Voice 12.5KHz	47-48 127-128 169-170 211-212 289-290 345-346 405-406 453-454 493-494 549-550 589-590 629-630 673-674 715-716 783-784 831-832 879-880	769.293750 769.793750 770.056250 770.318750 770.806250 771.156250 771.531250 771.831250 772.081250 772.431250 772.681250 772.931250 773.206250 773.468750 773.893750 774.193750 774.493750	799.293750 799.793750 800.056250 800.318750 800.806250 801.156250 801.531250 801.831250 802.081250 802.431250 802.681250 802.931250 803.206250 803.468750 803.893750 804.193750

Part 2, Appendix L

	Voice 12.5KHz	919-920	774.743750	804.743750
Worcester	Voice 12.5KHz	49-50	769.306250	799.306250
*,**	Voice 12.5KHz	125-126	769.781250	799.781250
	Voice 12.5KHz	165-166	770.031250	800.031250
	Voice 12.5KHz	209-210	770.306250	800.306250
	Voice 12.5KHz	281-282	770.756250	800.756250
	Voice 12.5KHz	321-322	771.006250	801.006250
	Voice 12.5KHz	365-366	771.281250	801.281250
	Voice 12.5KHz	421-422	771.631250	801.631250
	Voice 12.5KHz	477-478	771.981250	801.981250
	Voice 12.5KHz	537-538	772.356250	802.356250
	Voice 12.5KHz	585-586	772.656250	802.656250
	Voice 12.5KHz	625-626	772.906250	802.906250
	Voice 12.5KHz	701-702	773.381250	803.381250
	Voice 12.5KHz	741-742	773.631250	803.631250
	Voice 12.5KHz	785-786	773.906250	803.906250
	Voice 12.5KHz	825-826	774.156250	804.156250
	Voice 12.5KHz	877-878	774.481250	804.481250
	Voice 12.5KHz	917-918	774.731250	804.731250

County Notation	Band	FCC Channel Number	Base Frequency	Mobile Frequency
Androscoggin	Voice 12.5KHz	43-44	769.268750	799.268750
	Voice 12.5KHz	95-96	769.593750	799.593750
	Voice 12.5KHz	137-138	769.856250	799.856250
	Voice 12.5KHz	213-214	770.331250	800.331250
	Voice 12.5KHz	289-290	770.806250	800.806250
	Voice 12.5KHz	357-358	771.231250	801.231250
	Voice 12.5KHz	397-398	771.481250	801.481250
	Voice 12.5KHz	465-466	771.906250	801.906250
	Voice 12.5KHz	529-530	772.306250	802.306250
	Voice 12.5KHz	581-582	772.631250	802.631250
	Voice 12.5KHz	637-638	772.981250	802.981250
	Voice 12.5KHz	679-680	773.243750	803.243750
	Voice 12.5KHz	741-742	773.631250	803.631250
	Voice 12.5KHz	839-840	774.243750	804.243750
	Voice 12.5KHz	879-880	774.493750	804.493750
	Voice 12.5KHz	919-920	774.743750	804.743750
Aroostook	Voice 12.5KHz	17-18	769.106250	799.106250
	Voice 12.5KHz	57-58	769.356250	799.356250
	Voice 12.5KHz	97-98	769.606250	799.606250
	Voice 12.5KHz	169-170	770.056250	800.056250
	Voice 12.5KHz	209-210	770.306250	800.306250
	Voice 12.5KHz	249-250	770.556250	800.556250
	Voice 12.5KHz	289-290	770.806250	800.806250
	Voice 12.5KHz	345-346	771.156250	801.156250
	Voice 12.5KHz	401-402	771.506250	801.506250
	Voice 12.5KHz	449-450	771.806250	801.806250
	Voice 12.5KHz	493-494	772.081250	802.081250
	Voice 12.5KHz	533-534	772.331250	802.331250
	Voice 12.5KHz	601-602	772.756250	802.756250
	Voice 12.5KHz	669-670	773.181250	803.181250
	Voice 12.5KHz	717-718	773.481250	803.481250
	Voice 12.5KHz	757-758	773.731250	803.731250
	Voice 12.5KHz	797-798	773.981250	803.981250
	Voice 12.5KHz	837-838	774.231250	804.231250
	Voice 12.5KHz	877-878	774.481250	804.481250
	Voice 12.5KHz	917-918	774.731250	804.731250
Cumberland	Voice 12.5KHz	13-14	769.081250	799.081250
	Voice 12.5KHz	53-54	769.331250	799.331250
	Voice 12.5KHz	121-122	769.756250	799.756250
	Voice 12.5KHz	161-162	770.006250	800.006250
	Voice 12.5KHz	201-202	770.256250	800.256250
	Voice 12.5KHz	241-242	770.506250	800.506250

	Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice	12.5KHz 12.5KHz 12.5KHz 12.5KHz 12.5KHz 12.5KHz 12.5KHz 12.5KHz 12.5KHz 12.5KHz 12.5KHz 12.5KHz 12.5KHz 12.5KHz	281-282 349-350 409-410 473-474 517-518 557-558 601-602 661-662 705-706 781-782 821-822 863-864 905-906 945-946	770.756250 771.181250 771.556250 771.956250 772.231250 772.481250 772.756250 773.131250 773.406250 773.881250 774.131250 774.393750 774.656250 774.906250	800.756250 801.181250 801.556250 801.956250 802.231250 802.481250 802.756250 803.131250 803.406250 803.881250 804.131250 804.393750 804.656250 804.906250
Franklin	Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice	12.5KHz 12.5KHz	17-18 83-84 123-124 163-164 205-206 245-246 329-330 369-370 411-412 453-454 505-506 553-554 623-624 665-666 707-708 795-796 901-902 941-942	769.106250 769.518750 769.768750 770.018750 770.281250 770.531250 771.056250 771.306250 771.831250 772.156250 772.456250 772.456250 773.156250 773.156250 773.418750 773.968750 774.631250 774.881250	799.106250 799.518750 799.768750 800.018750 800.281250 801.056250 801.306250 801.568750 801.831250 802.156250 802.456250 802.456250 802.893750 803.156250 803.418750 803.968750 804.631250 804.881250
Hancock	Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice Voice		13-14 53-54 93-94 137-138 213-214 257-258 341-342 385-386 425-426 473-474 549-550 613-614 673-674 749-750 789-790 829-830 875-876 915-916	769.081250 769.331250 769.581250 769.856250 770.331250 770.606250 771.406250 771.656250 771.956250 772.431250 772.831250 773.206250 773.681250 773.931250 774.181250 774.718750	799.081250 799.331250 799.581250 799.856250 800.331250 800.606250 801.131250 801.406250 801.656250 801.956250 802.431250 802.831250 803.206250 803.681250 803.931250 804.181250 804.718750
Kennebec	Voice Voice	12.5KHz 12.5KHz 12.5KHz 12.5KHz	49-50 129-130 177-178 253-254	769.306250 769.806250 770.106250 770.581250	799.306250 799.806250 800.106250 800.581250

	Voice 12.5KHz Voice 12.5KHz	297-298 345-346 429-430 477-478 521-522 561-562 605-606 713-714 759-760 833-834 873-874 913-914	770.856250 771.156250 771.681250 771.981250 772.256250 772.781250 773.456250 773.743750 774.206250 774.456250 774.706250	800.856250 801.156250 801.681250 801.981250 802.256250 802.781250 803.456250 803.743750 804.206250 804.456250 804.706250
Knox	Voice 12.5KHz	125-126 165-166 243-244 285-286 325-326 373-374 413-414 457-458 541-542 597-598 639-640 701-702 743-744 783-784 823-824 903-904	769.781250 770.031250 770.518750 770.781250 771.031250 771.331250 771.581250 771.856250 772.381250 772.731250 772.993750 773.381250 773.381250 773.893750 773.893750 774.643750 774.643750	799.781250 800.031250 800.518750 800.781250 801.031250 801.331250 801.581250 801.856250 802.381250 802.731250 802.731250 802.993750 803.381250 803.643750 803.893750 804.143750 804.643750
Lincoln	Voice 12.5KHz	19-20 85-86 209-210 291-292 337-338 381-382 421-422 501-502 577-578 629-630 675-676 719-720 787-788 827-828 869-870	769.118750 769.531250 770.306250 770.818750 771.106250 771.381250 771.631250 772.131250 772.606250 772.931250 773.218750 773.493750 773.918750 774.168750 774.431250	799.118750 799.531250 800.306250 800.818750 801.106250 801.381250 801.631250 802.131250 802.606250 802.931250 803.218750 803.493750 803.918750 804.168750 804.431250
Oxford	Voice 12.5KHz Voice 12.5KHz	59-60 99-100 257-258 321-322 385-386 441-442 489-490 537-538 617-618 673-674 749-750	769.368750 769.618750 770.606250 771.006250 771.406250 771.756250 772.056250 772.356250 772.856250 773.206250 773.681250	799.368750 799.618750 800.606250 801.006250 801.406250 801.756250 802.056250 802.356250 802.856250 803.206250 803.681250

	Voice 12.	5VU-	789-790	773.931250	803.931250
	Voice 12.		867-868	774.418750	804.418750
	VOICE IZ.	JIIIZ	007-000	774.410730	004.410750
Penobscot	Voice 12.	5KHz	41-42	769.256250	799.256250
	Voice 12.		81-82	769.506250	799.506250
	Voice 12.		121-122	769.756250	799.756250
	Voice 12.		161-162	770.006250	800.006250
	Voice 12.		201-202	770.256250	800.256250
	Voice 12.		241-242	770.506250	800.506250
	Voice 12.		281-282	770.756250	800.756250
	Voice 12.		333-334	771.081250	801.081250
	Voice 12.	5KHz	377-378	771.356250	801.356250
	Voice 12.	5KHz	417-418	771.606250	801.606250
	Voice 12.	5KHz	461-462	771.881250	801.881250
	Voice 12.	5KHz	509-510	772.181250	802.181250
	Voice 12.	5KHz	573-574	772.581250	802.581250
	Voice 12.	5KHz	621-622	772.881250	802.881250
	Voice 12.	5KHz	661-662	773.131250	803.131250
	Voice 12.	5KHz	705-706	773.406250	803.406250
	Voice 12.	5KHz	745-746	773.656250	803.656250
	Voice 12.	5KHz	785-786	773.906250	803.906250
	Voice 12.	5KHz	861-862	774.381250	804.381250
	Voice 12.	5KHz	905-906	774.656250	804.656250
	Voice 12.	5KHz	947-948	774.918750	804.918750
Piscataquis	Voice 12.	5KHz	51-52	769.318750	799.318750
	Voice 12.	5KHz	133-134	769.831250	799.831250
	Voice 12.		173-174	770.081250	800.081250
	Voice 12.	5KHz	285-286	770.781250	800.781250
	Voice 12.	5KHz	325-326	771.031250	801.031250
	Voice 12.	5KHz	365-366	771.281250	801.281250
	Voice 12.	5KHz	409-410	771.556250	801.556250
	Voice 12.	5KHz	469-470	771.931250	801.931250
	Voice 12.	5KHz	517-518	772.231250	802.231250
	Voice 12.	5KHz	557-558	772.481250	802.481250
	Voice 12.	5KHz	609-610	772.806250	802.806250
	Voice 12.		701-702	773.381250	803.381250
	Voice 12.	5KHz	751-752	773.693750	803.693750
	Voice 12.		791-792	773.943750	803.943750
	Voice 12.	5KHz	831-832	774.193750	804.193750
	Voice 12.	5KHz	871-872	774.443750	804.443750
5.5	2				
Sagadahoc	Voice 12.		91-92	769.568750	799.568750
	Voice 12.		133-134	769.831250	799.831250
	Voice 12.		173-174	770.081250	800.081250
	Voice 12.		219-220	770.368750	800.368750
	Voice 12.		331-332	771.068750	801.068750
	Voice 12.		389-390	771.431250	801.431250
	Voice 12.		445-446	771.781250	801.781250
	Voice 12.		493-494	772.081250	802.081250
	Voice 12.		569-570	772.556250	802.556250
	Voice 12.		613-614	772.831250	802.831250
	Voice 12.		669-670	773.181250	803.181250
	Voice 12.		753-754	773.706250	803.706250
	Voice 12.	SKHZ	793-794	773.956250	803.956250
Compaget	T7-1- 10	EWII~	AE AC	760 001050	700 201050
Somerset	Voice 12.	ZHAC	45-46	769.281250	799.281250

	Voice 12.5KHz	89-90 139-140 217-218 259-260 353-354 393-394 437-438 497-498 545-546 593-594 633-634 677-678 825-826 865-866	769.556250 769.868750 770.356250 770.618750 771.206250 771.456250 772.106250 772.406250 772.706250 772.956250 773.231250 774.156250 774.406250	799.556250 799.868750 800.356250 800.618750 801.206250 801.456250 802.106250 802.406250 802.706250 802.956250 803.231250 804.156250 804.406250
	Voice 12.5KHz	909-910	774.681250	804.681250
Waldo	Voice 12.5KHz	57-58 97-98 169-170 249-250 361-362 401-402 449-450 491-492 533-534 585-586 625-626 667-668 709-710 755-756 797-798 837-838 943-944	769.356250 769.606250 770.056250 770.556250 771.256250 771.506250 771.806250 772.068750 772.331250 772.656250 772.906250 773.168750 773.431250 773.718750 773.981250 774.231250 774.893750	799.356250 799.606250 800.056250 800.556250 801.256250 801.506250 802.068750 802.331250 802.656250 802.906250 803.168750 803.431250 803.718750 803.981250 804.231250 804.893750
Washington	Voice 12.5KHz	49-50 129-130 177-178 219-220 297-298 357-358 433-434 481-482 521-522 565-566 637-638 713-714 753-754 821-822 869-870 911-912	769.306250 769.806250 770.106250 770.368750 770.856250 771.231250 771.706250 772.006250 772.256250 772.531250 772.981250 773.456250 773.706250 774.131250 774.693750	799.306250 799.806250 800.106250 800.368750 800.856250 801.231250 801.706250 802.006250 802.256250 802.531250 802.981250 803.456250 803.706250 804.131250 804.693750
York	Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz	45-46 93-94 169-170 249-250 293-294 341-342	769.281250 769.581250 770.056250 770.556250 770.831250 771.131250	799.281250 799.581250 800.056250 800.556250 800.831250 801.131250

401-402	771.506250	801.506250
449-450	771.806250	801.806250
	772.106250	802.106250
	772.406250	802.406250
	772.656250	802.656250
	772.906250	802.906250
	773.481250	803.481250
	773.731250	803.731250
		803.981250
		804.231250
		804.481250
	774.731250	804.731250
	401-402 449-450 497-498 545-546 585-586 625-626 717-718 757-758 797-798 837-838 877-878 917-918	449-450 771.806250 497-498 772.106250 545-546 772.406250 585-586 772.656250 625-626 772.906250 717-718 773.481250 757-758 773.731250 797-798 773.981250 837-838 774.231250 877-878 774.481250

County	Band	FCC Channel	Base	Mobile
Notation		Number	Frequency	Frequency
Belknap	Voice 12.5KHz Voice 12.5KHz	47-48 91-92 139-140 179-180 345-346 405-406 445-446 493-494 539-540 605-606 707-708 861-862	769.293750 769.568750 769.868750 770.118750 771.156250 771.781250 772.081250 772.368750 772.781250 773.418750 774.381250	799.293750 799.568750 799.868750 800.118750 801.156250 801.531250 801.781250 802.081250 802.368750 802.781250 803.418750 804.381250
Carroll	Voice 12.5KHz	15-16 85-86 125-126 209-210 287-288 353-354 421-422 463-464 513-514 555-556 595-596 635-636 701-702 903-904 943-944	769.093750 769.531250 769.781250 770.306250 770.793750 771.206250 771.631250 771.893750 772.206250 772.468750 772.718750 772.968750 773.381250 774.643750 774.893750	799.093750 799.531250 799.781250 800.306250 800.793750 801.206250 801.631250 801.893750 802.206250 802.468750 802.718750 802.968750 803.381250 804.643750 804.893750
Cheshire	Voice 12.5KHz	53-54	769.331250	799.331250
	Voice 12.5KHz	93-94	769.581250	799.581250
	Voice 12.5KHz	259-260	770.618750	800.618750
	Voice 12.5KHz	327-328	771.043750	801.043750
	Voice 12.5KHz	389-390	771.431250	801.431250
	Voice 12.5KHz	433-434	771.706250	801.706250
	Voice 12.5KHz	499-500	772.118750	802.118750
	Voice 12.5KHz	545-546	772.406250	802.406250
	Voice 12.5KHz	597-598	772.731250	802.731250
	Voice 12.5KHz	637-638	772.981250	802.981250
	Voice 12.5KHz	679-680	773.243750	803.243750
Coos	Voice 12.5KHz	247-248	770.543750	800.543750
	Voice 12.5KHz	291-292	770.818750	800.818750
	Voice 12.5KHz	337-338	771.106250	801.106250

	Voice 12.5KHz	377-378	771.356250	801.356250
	Voice 12.5KHz	433-434	771.706250	801.706250
	Voice 12.5KHz	501-502	772.131250	802.131250
	Voice 12.5KHz			
		549-550	772.431250	802.431250
	Voice 12.5KHz	589-590	772.681250	802.681250
	Voice 12.5KHz	667-668	773.168750	803.168750
	Voice 12.5KHz	709-710	773.431250	803.431250
	Voice 12.5KHz	783-784	773.893750	803.893750
	Voice 12.5KHz	829-830	774.181250	
				804.181250
	Voice 12.5KHz	907-908	774.668750	804.668750
	Voice 12.5KHz	947-948	774.918750	804.918750
O 5h	77. '	FD F0	E.C. 05.050	B00 055050
Grafton	Voice 12.5KHz	57-58	769.356250	799.356250
	Voice 12.5KHz	97-98	769.606250	799.606250
	Voice 12.5KHz	165-166	770.031250	800.031250
	Voice 12.5KHz	253-254	770.581250	800.581250
	Voice 12.5KHz	299-300	770.868750	800.868750
	Voice 12.5KHz	365-366		
			771.281250	801.281250
	Voice 12.5KHz	413-414	771.581250	801.581250
	Voice 12.5KHz	483-484	772.018750	802.018750
	Voice 12.5KHz	525-526	772.281250	802.281250
	Voice 12.5KHz	565-566	772.531250	802.531250
	Voice 12.5KHz	629-630	772.931250	802.931250
	Voice 12.5KHz	751-752	773.693750	803.693750
	Voice 12.5KHz	799-800	773.993750	803.993750
	Voice 12.5KHz	873-874	774.456250	804.456250
	Voice 12.5KHz	913-914	774.706250	804.706250
Hillsborough	Voice 12.5KHz	89-90	769.556250	799.556250
HIIISDOLOUGH				
	Voice 12.5KHz	219-220	770.368750	800.368750
	Voice 12.5KHz	291-292	770.818750	800.818750
	Voice 12.5KHz	349-350	771.181250	801.181250
	Voice 12.5KHz	409-410	771.556250	801.556250
	Voice 12.5KHz	469-470	771.931250	801.931250
	Voice 12.5KHz	517-518	772.231250	802.231250
	Voice 12.5KHz	561-562	772.506250	
				802.506250
	Voice 12.5KHz	609-610	772.806250	802.806250
	Voice 12.5KHz	669-670	773.181250	803.181250
	Voice 12.5KHz	781-782	773.881250	803.881250
	Voice 12.5KHz	833-834	774.206250	804.206250
P. 1921				
Merrimack	Voice 12.5KHz	17-18	769.106250	799.106250
	Voice 12.5KHz	123-124	769.768750	799.768750
	Voice 12.5KHz	173-174	770.081250	800.081250
	Voice 12.5KHz	245-246	770.531250	800.531250
	Voice 12.5KHz	295-296	770.843750	
				800.843750
	Voice 12.5KHz	357-358	771.231250	801.231250
	Voice 12.5KHz	397–398	771.481250	801.481250
	Voice 12.5KHz	453-454	771.831250	801.831250
	Voice 12.5KHz	533-534	772.331250	802.331250
	Voice 12.5KHz	573-574	772.581250	802.581250
	Voice 12.5KHz	621-622	772.881250	802.881250
	Voice 12.5KHz	713-714	773.456250	803.456250
	Voice 12.5KHz			
		793-794	773.956250	803.956250
	Voice 12.5KHz	839-840	774.243750	804.243750
	Voice 12.5KHz	901-902	774.631250	804.631250
	Voice 12.5KHz	941-942	774.881250	804.881250

Rockingham	Voice 12.5KHz	51-52	769.318750	799.318750
	Voice 12.5KHz	129-130	769.806250	799.806250
	Voice 12.5KHz	213-214	770.331250	800.331250
	Voice 12.5KHz	285-286	770.781250	800.781250
	Voice 12.5KHz	325-326	771.031250	801.031250
	Voice 12.5KHz	369-370	771.306250	801.306250
	Voice 12.5KHz	417-418	771.606250	801.606250
	Voice 12.5KHz	461-462	771.881250	801.881250
	Voice 12.5KHz	509-510	772.181250	802.181250
	Voice 12.5KHz	553-554	772.456250	802.456250
	Voice 12.5KHz	593-594	772.706250	802.706250
	Voice 12.5KHz	633-634	772.956250	802.956250
	Voice 12.5KHz	677-678	773.231250	803.231250
	Voice 12.5KHz	753-754	773.706250	803.706250
Strafford	Voice 12.5KHz	55-56	769.343750	799.343750
	Voice 12.5KHz	163-164	770.018750	800.018750
	Voice 12.5KHz	203-204	770.268750	800.268750
	Voice 12.5KHz	255-256	770.593750	800.593750
	Voice 12.5KHz	333-334	771.081250	801.081250
	Voice 12.5KHz	381-382	771.381250	801.381250
	Voice 12.5KHz	429-430	771.681250	801.681250
	Voice 12.5KHz	477-478	771.981250	801.981250
	Voice 12.5KHz	521-522	772.256250	802.256250
	Voice 12.5KHz	563-564	772.518750	802.518750
	Voice 12.5KHz	613-614	772.831250	802.831250
	Voice 12.5KHz	665-666	773.156250	803.156250
	Voice 12.5KHz	745-746	773.656250	803.656250
	Voice 12.5KHz	785-786	773.906250	803.906250
	Voice 12.5KHz	825-826	774.156250	804.156250
	Voice 12.5KHz	869-870	774.431250	804.431250
	Voice 12.5KHz	909-910	774.681250	804.681250
Sullivan	Voice 12.5KHz	41-42	769.256250	799.256250
	Voice 12.5KHz	81-82	769.506250	799.506250
	Voice 12.5KHz	133-134	769.831250	799.831250
	Voice 12.5KHz	201-202	770.256250	800.256250
	Voice 12.5KHz	341-342	771.131250	801.131250
	Voice 12.5KHz	383-384	771.393750	801.393750
	Voice 12.5KHz	425-426	771.656250	801.656250
	Voice 12.5KHz	505-506	772.156250	802.156250
	Voice 12.5KHz	551-552	772.443750	802.443750
	Voice 12.5KHz	603-604	772.768750	802.768750
	Voice 12.5KHz	743-744	773.643750	803.643750
	Voice 12.5KHz	823-824	774.143750	804.143750
	Voice 12.5KHz	863-864	774.393750	804.393750
	Voice 12.5KHz	919-920	774.743750	804.743750

County Notation	Band	FCC Channel Number	Base Frequency	Mobile Frequency
Bristol	Voice 12.5KHz Voice 12.5KHz	259-260 333-334 373-374 423-424 509-510 553-554 601-602 707-708 787-788 827-828 903-904	770.618750 771.081250 771.331250 771.643750 772.181250 772.456250 772.756250 773.418750 773.918750 774.168750 774.643750	800.618750 801.081250 801.331250 801.643750 802.181250 802.456250 802.756250 803.418750 803.918750 804.168750 804.643750
Kent	Voice 12.5KHz	15-16 167-168 213-214 255-256 325-326 367-368 417-418 461-462 523-524 587-588 713-714 753-754 821-822 947-948	769.093750 770.043750 770.331250 770.593750 771.031250 771.293750 771.606250 771.881250 772.268750 772.668750 773.456250 773.706250 774.131250 774.918750	799.093750 800.043750 800.331250 800.593750 801.031250 801.293750 801.606250 801.881250 802.268750 802.668750 803.456250 803.706250 804.131250 804.918750
Newport	Voice 12.5KHz	81-82 121-122 163-164 353-354 409-410 449-450 501-502 581-582 621-622 663-664 703-704 759-760 799-800 875-876 943-944	769.506250 769.756250 770.018750 771.206250 771.556250 771.806250 772.131250 772.631250 772.881250 773.143750 773.393750 773.743750 773.993750 774.468750 774.893750	799.506250 799.756250 800.018750 801.206250 801.556250 801.806250 802.131250 802.631250 802.881250 803.143750 803.393750 803.743750 803.993750 804.468750 804.893750
Providence	Voice 12.5KHz	19-20	769.118750	799.118750

	Voice 12.5KHz	93-94	769.581250	799.581250
	Voice 12.5KHz	135-136	769.843750	799.843750
	Voice 12.5KHz	179-180	770.118750	800.118750
	Voice 12.5KHz	249-250	770.556250	800.556250
	Voice 12.5KHz	293-294	770.831250	800.831250
	Voice 12.5KHz	341-342	771.131250	801.131250
	Voice 12.5KHz	397-398	771.481250	801.481250
	Voice 12.5KHz	437-438	771.731250	801.731250
	Voice 12.5KHz	485-486	772.031250	802.031250
	Voice 12.5KHz	529-530	772.306250	802.306250
	Voice 12.5KHz	569-570	772.556250	802.556250
	Voice 12.5KHz	637-638	772.981250	802.981250
	Voice 12.5KHz	677-678	773.231250	803.231250
	Voice 12.5KHz	747-748	773.668750	803.668750
	Voice 12.5KHz	861-862	774.381250	804.381250
	Voice 12.5KHz	909-910	774.681250	804.681250
Washington	Voice 12.5KHz	45-46	769.281250	799.281250
100	Voice 12.5KHz	87-88	769.543750	799.543750
	Voice 12.5KHz	127-128	769.793750	799.793750
	Voice 12.5KHz	205-206	770.281250	800.281250
	Voice 12.5KHz	299-300	770.868750	800.868750
	Voice 12.5KHz	361-362	771.256250	801.256250
	Voice 12.5KHz	405-406	771.531250	801.531250
	Voice 12.5KHz	469-470	771.931250	801.931250
	Voice 12.5KHz	561-562	772.506250	802.506250
	Voice 12.5KHz	607-608	772.793750	802.793750
	Voice 12.5KHz	671-672	773.193750	803.193750
	Voice 12.5KHz	743-744	773.643750	803.643750
	Voice 12.5KHz	783-784	773.893750	803.893750
	Voice 12.5KHz	833-834	774.206250	804.206250
	Voice 12.5KHz	879-880	774.493750	804.493750

21 1 6

		marketon star to here in a	RESOLUTION CO.	
0.22-20.000.000.000	5250 (1000) -	FCC Channel	Base	Mobile
County	Band	Number	Frequency	Frequency
Notation				
Addison	Voice 12.5KHz	49-50	769.306250	799.306250
Addison	Voice 12.5KHz	137-138	769.856250	799.856250
	Voice 12.5KHz	331-332	771.068750	801.068750
	Voice 12.5KHz	393-394	771.456250	801.456250
	Voice 12.5KHz	447-448	771.793750	801.793750
	Voice 12.5KHz	497-498	772.106250	802.106250
	Voice 12.5KHz	547-548	772.418750	802.418750
	Voice 12.5KHz	597-598	772.731250	802.731250
	VOICE 12.5KHZ	337-330	772.751250	002.751250
Bennington	Voice 12.5KHz	361-362	771.256250	801.256250
	Voice 12.5KHz	449-450	771.806250	801.806250
	Voice 12.5KHz	501-502	772.131250	802.131250
	Voice 12.5KHz	549-550	772.431250	802.431250
	Voice 12.5KHz	623-624	772.893750	802.893750
	Voice 12.5KHz	745-746	773.656250	803.656250
			F. CO. 0040F.	
Caledonia	Voice 12.5KHz	45-46	769.281250	799.281250
	Voice 12.5KHz	127-128	769.793750	799.793750
	Voice 12.5KHz	207-208	770.293750	800.293750
	Voice 12.5KHz	259-260	770.618750	800.618750
	Voice 12.5KHz	345-346	771.156250	801.156250
	Voice 12.5KHz	389-390	771.431250	801.431250
	Voice 12.5KHz	449-450	771.806250	801.806250
	Voice 12.5KHz	495-496	772.093750	802.093750
	Voice 12.5KHz	559-560	772.493750	802.493750
	Voice 12.5KHz	601-602	772.756250	802.756250
	Voice 12.5KHz	791-792	773.943750	803.943750
	Voice 12.5KHz	861-862	774.381250	804.381250
Chittenden	Voice 12.5KHz	19-20	769.118750	799.118750
	Voice 12.5KHz	89-90	769.556250	799.556250
	Voice 12.5KHz	161-162	770.006250	800.006250
	Voice 12.5KHz	205-206	770.281250	800.281250
	Voice 12.5KHz	257-258	770.606250	800.606250
	Voice 12.5KHz	349-350	771.181250	801.181250
	Voice 12.5KHz	405-406	771.531250	801.531250
	Voice 12.5KHz	453-454	771.831250	801.831250
	Voice 12.5KHz	517-518	772.231250	802.231250
	Voice 12.5KHz	573-574	772.581250	802.581250
	Voice 12.5KHz	625-626	772.906250	802.906250
	Voice 12.5KHz	669-670	773.181250	803.181250
	Voice 12.5KHz	713-714	773.456250	803.456250
	Voice 12.5KHz	753-754	773.706250	803.706250
	Voice 12.5KHz	797-798	773.981250	803.981250

	Voice 12.5KHz	865-866	774.406250	804.406250
	Voice 12.5KHz	905-906	774.656250	804.656250
	Voice 12.5KHz	945-946	774.906250	804.906250
	/			
Essex	Voice 12.5KHz	81-82	769.506250	799.506250
Dogen	Voice 12.5KHz	133-134	769.831250	799.831250
	Voice 12.5KHz	173-174	770.081250	800.081250
	Voice 12.5KHz	213-214	770.331250	800.331250
	Voice 12.5KHz	283-284	770.768750	800.768750
			771.031250	801.031250
	Voice 12.5KHz	325-326		
	Voice 12.5KHz	397-398	771.481250	801.481250
	Voice 12.5KHz	457-458	771.856250	801.856250
	Voice 12.5KHz	533-534	772.331250	802.331250
	Voice 12.5KHz	609-610	772.806250	802.806250
	Voice 12.5KHz	671-672	773.193750	803.193750
	Voice 12.5KHz	745-746	773.656250	803.656250
	Voice 12.5KHz	821-822	774.131250	804.131250
	Voice 12.5KHz	919-920	774.743750	804.743750
Franklin	Voice 12.5KHz	41-42	769.256250	799.256250
	Voice 12.5KHz	85-86	769.531250	799.531250
	Voice 12.5KHz	125-126	769.781250	799.781250
	Voice 12.5KHz	179-180	770.118750	800.118750
	Voice 12.5KHz	241-242	770.506250	800.506250
	Voice 12.5KHz	285-286	770.781250	800.781250
	Voice 12.5KHz	333-334	771.081250	801.081250
	Voice 12.5KHz	381-382	771.381250	801.381250
	Voice 12.5KHz	445-446	771.781250	801.781250
	Voice 12.5KHz	509-510	772.181250	802.181250
	Voice 12.5KHz	561-562	772.506250	802.506250
	Voice 12.5KHz	605-606	772.781250	802.781250
	Voice 12.5KHz	661-662	773.131250	803.131250
	Voice 12.5KHz	719-720	773.493750	803.493750
	Voice 12.5KHz	759-760	773.743750	803.743750
	Voice 12.5KHz	869-870	774.431250	804.431250
	Voice 12.5KHz	917-918	774.731250	804.731250
	10100 101010			
Grand Isle	Voice 12.5KHz	97-98	769.606250	799.606250
	Voice 12.5KHz	213-214	770.331250	800.331250
	Voice 12.5KHz	281-282	770.756250	800.756250
	Voice 12.5KHz	321-322	771.006250	801.006250
	Voice 12.5KHz	361-362	771.256250	801.256250
	Voice 12.5KHz	437-438	771.731250	801.731250
	Voice 12.5KHz	501-502	772.131250	802.131250
			772.131250	802.456250
	Voice 12.5KHz	553-554		
	Voice 12.5KHz	617-618	772.856250	802.856250
	Voice 12.5KHz	673-674	773.206250	803.206250
	Voice 12.5KHz	745-746	773.656250	803.656250
	Voice 12.5KHz	787-788	773.918750	803.918750
	Voice 12.5KHz	879-880	774.493750	804.493750
*	77-1 40 E777	15 16	760 003750	700 003750
Lamoille	Voice 12.5KHz	15-16	769.093750	799.093750 801.231250
	Voice 12.5KHz	357-358	771.231250	
	Voice 12.5KHz	411-412	771.568750	801.568750
	Voice 12.5KHz	461-462	771.881250	801.881250
	Voice 12.5KHz	503-504	772.143750	802.143750
	Voice 12.5KHz	545-546	772.406250	802.406250

	Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz	591-592 635-636 675-676 741-742 785-786 825-826 901-902	772.693750 772.968750 773.218750 773.631250 773.906250 774.156250 774.631250	802.693750 802.968750 803.218750 803.631250 803.906250 804.156250 804.631250
Orange	Voice 12.5KHz Voice 12.5KHz	131-132 175-176 217-218 321-322 437-438 491-492 537-538 577-578 673-674 717-718 757-758 827-828 867-868		799.818750 800.093750 800.356250 801.006250 801.731250 802.068750 802.356250 802.606250 803.206250 803.481250 803.731250 804.168750 804.418750
Orleans	Voice 12.5KHz	51-52 91-92 139-140 201-202 255-256 329-330 373-374 425-426 465-466 521-522 569-570 621-622 665-666 705-706 877-878 941-942	769.318750 769.568750 769.868750 770.256250 770.593750 771.056250 771.331250 771.656250 771.906250 772.256250 772.556250 772.881250 773.156250 773.406250 774.481250 774.881250	
Rutland	Voice 12.5KHz Voice 12.5KHz	59-60 129-130 177-178 251-252 385-386 457-458 541-542 633-634 677-678 755-756 821-822 869-870	769.368750 769.806250 770.106250 770.568750 771.406250 771.856250 772.381250 772.956250 773.231250 773.718750 774.131250 774.431250	799.368750 799.806250 800.106250 800.568750 801.406250 801.856250 802.381250 802.956250 803.231250 803.718750 804.131250 804.431250
Washington	Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz	121-122 169-170 249-250 335-336 417-418	769.756250 770.056250 770.556250 771.093750 771.606250	799.756250 800.056250 800.556250 801.093750 801.606250

	Voice 12.5KHz	473-474	771.956250	801.956250
	Voice 12.5KHz	529-530	772.306250	802.306250
	Voice 12.5KHz	585-586	772.656250	802.656250
	Voice 12.5KHz	679-680	773.243750	803.243750
	Voice 12.5KHz	747-748	773.668750	803.668750
	Voice 12.5KHz	833-834	774.206250	804.206250
	Voice 12.5KHz	909-910	774.681250	804.681250
Windham	Voice 12.5KHz	205-206	770.281250	800.281250
	Voice 12.5KHz	285-286	770.781250	800.781250
	Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz	353-354 395-396 473-474	771.206250 771.468750 771.956250 772.268750	801.206250 801.468750 801.956250 802.268750
	Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz Voice 12.5KHz	523-524 589-590 671-672 829-830	772.200750 772.681250 773.193750 774.181250	802.681250 803.193750 804.181250
Windsor	Voice 12.5KHz	909-910 13-14	774.681250 769.081250	804.681250 799.081250
	Voice 12.5KHz	87-88	769.543750	799.543750
	Voice 12.5KHz	373-374	771.331250	801.331250
	Voice 12.5KHz	465-466	771.906250	801.906250
	Voice 12.5KHz	515-516	772.218750	802.218750
	Voice 12.5KHz	557-558	772.481250	802.481250
	Voice 12.5KHz	613-614	772.831250	802.831250
	Voice 12.5KHz	665-666	773.156250	803.156250
	Voice 12.5KHz	705-706	773.406250	803.406250
	Voice 12.5KHz	789-790	773.931250	803.931250